AMERICAN

SEPTEMBER • 1955

Cinematographer

THE MAGAZINE OF MOTION PICTURE PHOTOGRAPHY

This Issue . . .

- Exposure Determination for Variable Shutter Speeds
- Make-up For Today's Color Films
- Pre-printing Preparation of Home Films

25c

FOREIGN 35

VETERAN CAMERAMAN MARCEL BEQUEE, left, and Assistant Fred Montague are working in extreme heat as they film glass-block production. "We always shoot with 'Superior' 2," comments Rebiere, who shot the first "March of Time," "because the film is so good that it performs perfectly no matter what temperatures we run into while telling the photo story of American industry."

"We couldn't shoot in extremes of light and temperature without **Du Pont 'Superior' 2 Film!**"

says **Arthur J. Lodge, Jr.,** *Producer of the Peabody Award Winner "Industry on Parade."*

IN CUTTING ROOM, Producer Arthur Lodge, left, shows product to G. W. "Johnny" Johnstone, center, Radio-Television Public Relations Director of the National Association of Manufacturers—sponsors of "Industry on Parade." At right, N.A.M.'s Newsreel Editor Roger Young is impressed with finished film . . . the result of using "Superior" 2.

"On the same day I've had one crew contending with 200° heat in a steel mill while another was filming at 20° below zero in a bakery's bread-freezing room," recalls Arthur Lodge. "But rugged 'Superior' 2 keeps our cameras rolling in every conceivable location—planes, submarines, coal and iron mines, steel mills and rubber plants. Its consistent speed and gradation enable us to shoot with confidence far ahead of our lab schedule."

It takes 20 cameramen shooting film at the rate of 4,000 feet a week to keep more than 241 television stations supplied with the popular "Industry on Parade" 15-minute program.

"Our crews get film shipped to them from Du Pont offices all over the country," Producer Lodge goes on. "Both before and after exposure the film is subjected to intense heat and cold . . . to dampness and rough riding in auto trunks. Yet, frame for frame, the results are always consistent enough to run on the same reel.

"Another advantage of using Du Pont Film is the customer service extended by Du Pont representatives. It means so much whenever we need broken lots or superfast delivery."

FOR MORE INFORMATION about "Superior" 2 and other Du Pont Films . . . write or call the nearest District Office (listed below) or the Du Pont Company, Photo Products Department, Wilmington 98, Delaware. In Canada: Du Pont Company of Canada Limited, Montreal.

DISTRICT OFFICES

ATLANTA 5, GA.	805 Peachtree Bldg.
BOSTON 10, MASS.	140 Federal Street
CHICAGO 18, ILL.	3280 N. California Ave.
CLEVELAND 14, OHIO	1836 Union Commerce Bldg.
DALLAS 7, TEXAS	1628 Oak Lawn Ave.
LOS ANGELES 38, CALIF.	7851 Santa Monica Blvd.
NEW YORK 11, N. Y.	248 West 18th Street
PHILADELPHIA 2, PA.	225 South 15th Street

DU PONT

Better Things for Better Living . . . through Chemistry

DU PONT MOTION PICTURE FILM

PROFESSIONAL JUNIOR

-MOST *imitated* tripod in the world!

They've been standing on their heads, trying to copy PROFESSIONAL JUNIOR Tripod—but nobody can get around our exclusive patented features.

Features which make PROFESSIONAL JUNIOR tops in the motion picture, TV and commercial film world. First choice of professional cameramen. First choice of our Armed Forces.

Is your work "dragging" for want af an outstanding tripod? Get PROFESSIONAL JUNIOR— *the price hasn't changed in 15 years.* Get it today.

Professional Juniar
GEARED HEAD
interchangeable with Frictian Head on same tripad.

New Professional Juniar Adjustable wood
BABY TRIPOD
—far friction and geared Heads.
Has substantial shae and spur.
Measures from floar ta flange 25" extended—17" callapsed.

FRANK C. ZUCKER
CAMERA EQUIPMENT CO.
Dept. A-9-18 • 1600 Broadway • New York City



AMERICAN

Cinematographer

THE MAGAZINE OF MOTION PICTURE PHOTOGRAPHY
PUBLICATION OF THE AMERICAN SOCIETY OF CINEMATOGRAPHERS

ARTHUR E. GAVIN, *Editor*
MARION HUTCHINS, *Editorial Assistant* EMERY HUSE, *Technical Editor*
EDITORIAL ADVISORY BOARD: John Arnold, Arthur Edeson, Lee Garmes, Charles Rosher, Leon Shamroy, Fred Gage, Glenn R. Kershner

Editorial and Business Office: 1782 N. Orange Dr., Hollywood 28, Calif.
Telephone: HOllywood 7-2135

VOL. 36 SEPTEMBER • 1955 NO. 9

In This Issue

ARTICLES

EXPOSURE DETERMINATION FOR VARIABLE SHUTTER SPEEDS—*By Frank P. Fritz* 524
MAKE-UP MAGIC FOR TODAY'S COLOR FILMS—*By Walter Ramsey* 526
PRE-PRINTING PREPARATION OF 16MM FILMS 531
PHOTOGRAPHY AT 40,000 FEET—*By William Daniels, A.S.C.* 532
FILMING "THE AFRICAN LION" 534
INNOVATIONS HIGHLIGHT NEW S6 MAGNETIC RECORDER—*By Frederick Foster* 536

AMATEUR CINEMATOGRAPHY

FILMING A PRIZE WINNER—*By Clifford V. Harrington* 538
SHOOTING MOVIES FROM THE AIR—*By Dean Riggins* 540

FEATURES

HOLLYWOOD BULLETIN BOARD 508
WHAT'S NEW IN EQUIPMENT, ACCESSORIES, SERVICE 510
INDUSTRY NEWS 520
HOLLYWOOD STUDIO PRODUCTION 554

ON THE COVER

CINEMATOGRAPHER William Mellor, A.S.C. and his camera assistants line up a closeup shot of Elizabeth Taylor and Rock Hudson for "Giant," which producer-director George Stevens (right) is producing for Warner Brothers. Stately Virginia manor house near Charlottesville provides background for the romantic action here. *Photo by Floyd McCarty*

AMERICAN CINEMATOGRAPHER, established 1920, is published monthly by the A. S. C. Agency, Inc., 1782 N. Orange Dr., Hollywood 28, Calif. Entered as second class matter Nov. 18, 1937, at the postoffice at Los Angeles, Calif., under act of March 3, 1879. SUBSCRIPTIONS: United States and Canada, $3.00 per year; Foreign, including Pan American Union, $4.00 per year. Single copies, 25 cents; back numbers, 30 cents; foreign single copies, 35 cents; back numbers, 40 cents. Advertising rates on application.

Copyright 1955 by A. S. C. Agency, Inc.

PROUDLY CREATED TO *Outperform!*

Mitchell* CAMERAS



The matchless technical perfection which a Mitchell camera brings to a film can improve the investment as can no other single element of production.

For over 25 years constant research and engineering by Mitchell has continued to produce, year after year, the most advanced and only truly professional motion picture camera. It is traditional of Mitchell cameras that in addition to filming the world's greatest films, they are to be found wherever new and exacting techniques of filming are being successfully used.

Mitchell cameras are today dependably serving such varied fields as Television, Business and Industry, Education, the Armed Services, and major Motion Picture Studios.

Tom Kelley Studios shooting a commercial for North American Airlines with this Mitchell 35 "NC". Ceasar Romero is shown at center

Mitchell 35mm [illegible] Productions on the "I Love Lucy" series with Desi Arnaz, right and Lucille Ball

the 1 and only Mitchell

[illegible] Mitchell cameras are completely [illegible] and [illegible] 35 mm. Available [illegible] the finest of professional accessories.

Mitchell Camera CORPORATION

666 WEST HARVARD STREET • GLENDALE 4, CALIFORNIA • CABLE ADDRESS: "MITCAMCO"

85% of the motion pictures shown in theatres throughout the world are filmed with a Mitchell

Manufacturers and Distributors of:

- Blaap Punches
- Cans, Film Strip
- Editing Tables
- Film Bins
- Film Racks
- Flanges
- Film Editing Glaves
- Leader Stack, 16 & 35 mm
- Measuring Machines
- Plastic Cares, 16 & 35 mm
- Reels, 16 & 35 mm
- Reels, Nan-Magnetic
- Split Reels
- Rewinds
- Saund Readers
- Splicers
- Storage Cabinets
- Vault Cans
- Scatch Tape
- Clath Tape
- Saund Recarding Tapes

HOLLYWOOD FILM COMPANY

956 NO. SEWARD ST.
HOLLYWOOD 38, CALIF

precision film editing equipment

HO-23284

1

PERMA-LOCK MIRROR GUARANTEES POSITIVE MIRROR ALIGNMENT

Only a Perma Lock snaps into position and stays in position This insures positive mirror alignment, perfect focus after every globe removal Even a severe jolt can't disalign mirror

only J.G. McAlister spots combine all 3



2

LIFETIME BEAM-PILOTS GUARANTEE FLARE-FREE SPILL-PROOF LIGHTING

Encircling every Fresnel lens-zone are special, opaque bands, fused to the glass. These Beam Pilots prevent flare and spill-light by controlling side-beam deflection, and without losing useful light.

3

DUAL CONTROL FOCUSES BOTH FRONT AND REAR

New dual-focus control is twice as convenient, twice as accurate as unsteady, old-fashioned one lever focusing. Even Action focus is always smooth absolutely precise and accurate from spot to flood positions

TODAY, WRITE FOR COLORFUL NEW CATALOG-BROCHURE "NEW DIMENSIONS IN CONTROLLED STUDIO LIGHTING"

world headquarters for the finest engineered lighting & production equipment (sales and rentals).

J.G. McAlister Inc.

1117 North McCadden Place
Hollywood 38, California

BROOKS

BROOKS first for Every Photographic Need!

NEW ARRIFLEX 16

The only 16mm camera providing through-the-lens focusing and viewing during exposure, electric motor drive with matte box, cables $1650.00

16mm Xenon f/1.9 lens $ 170.00
25mm Xenon f/1.5 lens 200.00
75mm Xenon f/2 lens

AURICON-CINE VOICE

100 ft. mag. camera
New $695.00
Used 575.00

Auricon-Pro, 600 ft Mag Camera New $1165.00

Auricon Super, 1200 ft Mag Camera 1319.25

Model SW 602, 16mm film transport with center tracking Complete in parts bla case $1275.00

Other Model Prices on request

MAGNASYNC Model 400X—Portable $895.00

BUDGET TERMS AVAILABLE

COLORTRAN SPOT KIT

The "750" Spot Kit contains 3 spotlights with a Senior or Junior, plus 4 stands Snoots and diffusion for the spots are included $252.75

LENSES:

Kilar 150mm f/3.5 lens $119.95
Kilar 300mm f/5.6 lens 149.95
Kilar 400mm f/5.9 lens 239.95
Kilar Pan Cinar from 20mm to 60mm f/2.8 lens 349.00
Baiex Pan Cinar from 20mm to 60mm f/2.8 lens 880.00
Zoomar 16 25mm to 75mm f/2.9 lens 210.00
Astra 50mm f/2 295.00
Astra 100mm f/2 395.00
Astro 300mm f/3.5

The West's Biggest Display of Cameras and Photo Equipment

Store Hours 9 a.m. to 6 p.m.
Mondays 9 a.m. to 9 p.m.

BROOKS Cameras

45 KEARNY AT MAIDEN LANE
SAN FRANCISCO, CALIFORNIA
PHONE EXbrook 2-7348

Hollywood Bulletin Board

TWO PRIZE CAMERAMEN—Leyal Griggs, A.S.C., (right) Academy Award winning cinematographer, was visited on the set of "The Ten Commandments" at Paramount Studio last month by Paramount Newsreel cameraman V Parkash, who won Britain's Academy Award for his camera coverage of the funeral of Mahatma Ghandi Parkash is on route back to New Delhi, India after a year on leave in the United Nations in New York Here Griggs shows him the new VistaVision camera

• • •

The A.S.C., last month, admitted to membership Ray Foster (Active), Norwood L. Simmons, of Eastman Kodak Co. (Associate), and Walter F. Farley, Jr., of Eastman Kodak Co. (Associate).

• • •

Mack Stangler, A.S.C. is again shooting the "Liberace Show" for Guild Films, Inc. Stengler directed the photography of this popular TV film show last season, and will shoot it this year in addition to the "Ina Ray Hutton Show" and "It's Fun to Reduce," also for Guild.

• • •

WILLIAM SKALL A.S.C.

William Skall, A.S.C. is the latest top-flight feature film director of photography to swing to TV film production Skall has been signed to photograph the "Father Knows Best" series of TV films for Screen Gems, producing at Columbia Studio, Hollywood.

Leon Shamroy, A.S.C., three-time Academy Award winner, played a hero's role on the set last month when he took the brunt of a blow from a falling spotlight lens, which otherwise would have injured actress Jennifer Jones Incident occurred during shooting of scene for 20th Century-Fox's "Good Morning, Miss Dove," directed by Henry Koster and starring Miss Jones

• • •

Philip Tannura, A.S.C., started his fifth consecutive year as director of photography of "The Burns and Allen Show" when the company started shooting its new series at General Service Studio last month Shooting of first show in the 1955-56 series was marked by innovation of using background projection—rare for TV film production. Company plans to utilize system in more and more of its shows, according to Tannura.

• • •

CHARLES ROSHER A.S.C.

Charles Rosher, A.S.C., was cited last month by Photographer's Association of America "for his artistry and skill as the cinematographer who brought to the screen a host of motion picture classics, for his activity as a founder of the American Society of Cinematographers; and in recognition of his long membership in the PAA, reaching back to the turn of the century."

• • •

Dan Clark, A.S.C., photographed the pilot film of Edgar Bergen's new TV show, tentatively titled "Do You Trust Your Wife?" A quiz-type show, it was photographed in the same studio in which the Groucho Marx show is filmed each week. Like the latter, the Bergen show is filmed with eight cameras (4 on and 4 off) with the audience participating.

Safety...10 miles high!

. . . assured by Turco's Flaw Detection Method filmed at Northrop Aircraft with Auricon 16mm Sound Cameras



Cralen Enterprises, Inc., filming William Cox of Northrop Public Relations, as he interviews Robert Love, jet ace, after test flight in Northrop F-89 all-weather interceptor

The full story of flaw detection in metals with Turco "Dy-Chek" Dye Penetrant is the subject of a new Training Movie in sound and color, filmed at Northrop Aircraft with Auricon 16mm Sound-On-Film Cameras.

The film shows how "Quality-Control" checks metal parts for the Northrop F-89 all weather jet interceptor right on the production line, with Turco's "Dy-Chek" inspection process!

Turco's new Training Movie on "Dy-Chek" Flaw-Inspection Process, is shown during filming at Northrop Aircraft, with Craig Curtis (at camera) and Lennie Blondheim, both of Cralen Enterprises, Inc., Hollywood, California

This film is another example of how Training Movies and Industrial Motion Pictures can be produced with precision and fidelity using Auricon 16mm Sound Cameras. Professional Auricon Built-in Features, include Self-blimping Camera design, Synchronous Motor Drive, Auricon-Electromatic Take-up, etc. Many producers and cameramen have named Auricon . "the finest 16mm Sound Camera ever built!"

Auricon Cameras are sold with a 30-day money-back guarantee. You must be satisfied! Write for free illustrated Auricon catalog.

Auricon Hollywood

Auricon

A PRODUCT OF

BERNDT-BACH, INC.

6902 Romaine Street, Hollywood 38, California

MANUFACTURERS OF SOUND-ON-FILM

WHAT'S NEW

. . . in equipment, accessories, service



Cine-Voice Conversion

Filmtronics, Inc., 96 Huntington St., New London, Conn., offer a 400-ft. conversion of the Auricon Cine-Voice camera for newsreel, TV film and other professional uses.

The camera is cut down to the lowest possible point to minimize strain on the motor. The case is squared off at the ends for improved appearance and compactness and to enhance the camera's overall styling.

Features include 400-ft. magazine affording 10 minutes continuous recording; no extra motor drive; hinged door; improved footage counter; internal blimping; neon signal light; sound track exposure lamp switches off and on automatically with camera motor; turret rotating handle; and improved film guide rollers.

List price is $695 with 400-ft. magazine, $513 without magazine.

Cooler Projection Lamp

Sylvania Electric Products, Inc., announce a new ceramic-top projection lamp for home movie and slide projectors. Tradenamed the Blue Top projection lamp, because of a jewel-hard ceramic "bonnet" bonded to the glass, the lamp concentrates maximum light opposite the lens, creating a brighter, clearer image on the screen.

The blue ceramic "bonnet" is baked on and will not chip, scratch or peel, even after many hours of steady operation. This "bonnet" innovation dissipates heat more efficiently and prevents light leakage. New lamp is available in a full range of sizes and types to fit all projectors.

Rack-over for B&H Cameras

Cine Products Co., P.O. Box 135, Westlake, Ohio, offers a precision rack-over for Bell & Howell model 70 cameras, which is also adaptable to the Bolex H-8 and H-16 cameras. Device mounts on standard tripods. Cam locks in position to avoid accidental loss of field. List price is $28.50.

Video Film Labs Move

Video Film Laboratories, which since 1949 has been servicing east coast film makers with 16mm reversal processing, and 16mm negative and positive film developing, have moved to larger quarters from 131 West 23rd St., N. Y. City, to 350 West 50th Street, New York, N. Y.

16mm CinemaScope Lens

A 16mm CinemaScope projection lens adaptable to all popular 16mm projectors is offered by Bausch & Lomb Optical Co., Rochester, N. Y. Lens is a combination prime and anamorphic single-barrel lens and is offered in 2-inch focal length. It may be had in other focal lengths on order.

Lens requires no brackets or supports, is 6⅞" in length and weighs 7¾ ounces. List price with one adapter is $124.50. (Cut shows lens with an assortment of adapters.)

Editor Frame Counter

For use by Methods Engineers and others who use 16mm motion pictures for time and motion study, an accessory frame counter is now available for the Craig Projecto-Editor, Model KE-16. Each unit digit on the counter will either add or subtract. Counter can be set at zero. List price is $37.50. Manufacturer is the Kalart Company, Inc., Plainville, Conn.

Anti-static Solution

Anti-Stat #6 is tradename of product announced by Braun Laboratories recommended for use in eliminating dust and static from all metal, glass, plastic and film surfaces. Packed in 12 oz. aerosol spray can, list price is $2.95.

16mm Continuous Projector

A new 16mm projector designed to improve quality of TV film programs by providing a continuous, uniformly-illu-

(Continued on Page 512)

THE NATION'S

"Capital"



THE SERVICE LAB THAT SERVES THE NATION

- Scotch Trock Process
- RCA Sound Recording
- Scientific Processing
- Creative Editing
- Matchless Printing

capital

PRINTS BY CAPITAL

FILM LABORATORIES, INC.

Formerly McGeary Smith Laboratories, Incorporated

1905 Fairview Ave. N. E., Washington 2, D. C.

WRITE FOR OUR LATEST PRICE LIST AND ILLUSTRATED BROCHURE

QUALITY
is our business
Plus
personalized
service

in the East it's...

MOVIELAB

ROUND-THE-CLOCK SERVICES
Negative Developing
First Print Department
Ultra Violet and Flash Patch Printing
16mm and 35mm Release Printing
Kodachrome Printing
63 Editing Rooms
SPECIAL TV SERVICES

For Color it's
Rainbowlab Inc.

Now Celebrating Our 25th Anniversary

MOVIELAB FILM LABORATORIES, INC.
619 West 54th Street, New York 19, N. Y. JUdson 6-0360

WHAT'S NEW

. . in equipment, accessories, service

(Continued from Page 510)

minated image, is announced by Eastman Kodak Co., Rochester, N. Y. Operating at 24 f.p.s., mechanism is driven by 1800 r.p.m. synchronous motor which is loosely coupled to a small sync motor in the sound head to keep the two motors in phase during starting and stopping.

Complete data and price may be had by directing inquiry to Eastman Kodak Motion Picture Sales Dept.

35mm Projector Bargain

Semler Industries, Inc., 6853 Lankershim Blvd., North Hollywood, Calif., offers a limited number of U. S. Navy surplus 35mm Holmes projectors at the bargain price of $114.50. Machines are in first class shape, ready for instant use, have mazda lamps, and standard film magazines, but no amplifier or speaker.

8mm Reels and Cans

Eastman Kodak Company, through its retail outlets, are again making available 200- and 400-foot 8mm metal reels and cans for those who prefer metal instead of plastic. Cans are 50¢ and 80¢ each without reels, or $1.15 and $1.75 with reels.

Company states that the plastic reels and cans will continue to be available.

Filmline Processor

Filmline Corp., Erna St., Milford, Conn., announce its Model R15 16mm film processor with a capacity of 900 ft. per hour. Features include new type overdrive, removable magazines for daylight operation, and solution units re-

(Continued on Page 514)

F & B PRO CINE — THE MOST

IMPROVED



TRIPOD IN THE MEDIUM WEIGHT CLASS

FOR ALL CAMERAS

Does your tripod include these exclusive PRO CINE features?

A. External camera tightening knob with angle gears
B. Telescoping, offset tripod handle
C. Second tripod handle position
D. Large positive pan and tilt locks
E. Brass shaft for longer wear, no sticking
F. Separate, precision machined friction plate
G. Four bolted leg supports with leg rest ledge
H. Aluminum leg tops—no holes drilled thru wood legs
I. Single knob leg tightening—for even tension and no warping
J. Superb, seasoned and waxed hardwood legs, will never stick.

Finest Precision Craftsmanship and Materials

FRICTION HEAD UNCONDITIONALLY GUARANTEED FOR FIVE YEARS

MADE IN U.S.A.
EXCLUSIVELY BY F&B

Price **$145.00**
Heavy Duty Fibre Case **$20.00**

Available direct or at leading camera dealers

F & B SPLIT REELS



Ever Have the Center Drop Out?

Eliminates FLANGES and risky TIGHTWINDS

Simply open Split Reels—slip in film an care and work with safety, speed and accuracy.

400 ft.	SPLIT	REEL		$4.50
800	"	"	"	6.00
1200	"	"	"	7.50
1600	"	"	"	9.00

IMMEDIATE DELIVERY

New the
LARGEST STREET-LEVEL SHOWROOM IN NEW YORK
devoted exclusively to **MOTION PICTURE EQUIPMENT**. Some of the expanded facilities we will offer to film personnel are these:

COMPLETE RENTAL SERVICE . . . Cameras lighting editing, recording and grip equipment

CONVENIENCE . . . Street level, midtown location . . . Have your crews assemble at F&B

EXPERIENCED TECHNICAL PERSONNEL . . . who understand your filming problems

COMPLETE EQUIPMENT MAINTENANCE & ENGINEERING SHOPS . . . Staffed by ex Part technicians

NEW CREDIT PURCHASE FACILITIES . . . extended time payment service from 90 days to 36 months

LOCATED IN MIDTOWN MANHATTAN . . . Near all transportation hotels and recreation centers

F&B EQUIPMENT CATALOG—24 Pages . . . Lists all equipment you need for film production

F&B RENTAL PRICE LIST—16 Pages . . . Complete pocket size list. Everything at your fingertips about the cost of renting equipment for Production, Projection, Recording, Lighting and Editing

BOTH CATALOGS FREE FOR THE ASKING

SHOOTING COLOR IN A CAVE!

HUGE INDUSTRIAL INTERIORS

AUDIENCE REACTION SHOTS

COLOR NEWSREELS

F & B NOMINAR 1" f/0.95 LENS

In C mount for all 16mm cameras
"THE FASTEST CINE LENS IN THE WORLD"
More than twice as fast as f/1.4

Definition, resolution and contrast as good as better than any comparable lens

Price **$165.00** **$9.90** *FET*

Including—
Series VI filter holder, sunshade
Screw-on dust covers
Leather carrying case

F&B

FLORMAN & BABB
68 West 45th Street, New York 36, N. Y.
Phone: Murray Hill 2-2928
Cable Address — FLORBABB, N. Y.

ONE CAMERA

16mm or 35mm

in 10 SECONDS!

Camerette 16/35

Reflex Motion Picture Camera

The perfect camera for the motion picture film maker working in both 16mm or 35mm color or black and white

LOOK AT THESE ADVANTAGES—

- The same lenses, same motor drives, same sound blimp and accessory equipment used for both 16mm or 35mm — to convert simply change the magazine
- Precise rugged movement
- Reflex viewing
- 200 degree adjustable shutter
- Divergent three lens turret
- Automatic film gate 400′ magazines 16 or 35mm — the 16mm magazine will accommodate daylight spools as well as standard core load.
- Light weight — only 14 pounds with 3 lenses, 400′ magazine, and 6/8 volt motor

Write for brochure



Camerette

patents coutaat-mathat

Manufactured by Ets. Cine. Eclair, Paris

FRANK C. ZUCKER

CAMERA EQUIPMENT CO.

1600 BROADWAY NEW YORK CITY

(Continued from Page 512)

movable for easy cleaning. Size of processor is 76″ by 48″ by 24″. Weight is 450 lbs., crated. Price is $2495, F.O.B. factory. Descriptive literature is available.

How-To-Do-It Books

A complete series of low-priced "how-to-do-it" books for amateur movie makers is announced by the American Photographic Book Publishing Co., Inc., 33 West 60th St., New York 23, N. Y.

Each of the 12 books have been written by photographic experts able to write about their advanced techniques in a way that can be understood by even the beginning cine amateur. Each volume has been carefully illustrated and diagrammed to simplify or improve amateur movie making procedures.

Following are titles of the 12 books which sell for $1.75 each:

How to Make Home Movies.
How to Direct Your Own Movies.
How to Title Your Own Movies.
How to Make 8mm Movies.
How to Plan a Home Movie Script.
How to do Home Movie Tricks.
How to Make Good Color Movies.
How to Edit Your Own Movies.
How to Make Vacation Movies.
How to Make Movie Cartoons.
How to Act for Home Movies.
How to Add Sound to Your Home Movies.

16mm-35mm Sound Reader

An optical sound reader for 16mm and 35mm films selling for $119.50 is offered by Filmtronics, Inc., 96 Huntington St., New London, Conn.

Specifications and features include 115-v 60 cyc. AC operation; power consumption, 35 watts; uses CE-25 C photocell; 2-watt power output; fused for safety; highly polished drum with needle-point bearing; narrow width (4″ wide) allows reader to be placed close to most viewers for synch editing.



Movie Frame Copier

A precision optical device for copying frames of uncut 16mm color or black-and-white movie film onto 35mm still camera film is announced by Century Photographic Equipment Co., 10427 Burbank Blvd., North Hollywood, Calif. Trade-named the Duplikin, models are available for use with Exakta, Leica, Contax, Pentacon, Practika, and Canon 35mm cameras. List price is $39.50.

Film Processors

An economical, low-priced line of automatic 16mm reversal, negative-positive film processing machines is announced by Milford Film Machine, P.O. Box 343, Milford, Conn. Equipment features daylight operation, quality controls, slip-clutch film drive, and automatic operation. Prices start at $800, F.O.B. factory. Descriptive brochure is available.



CAMERETTE

Now Available with Two Important New Features!

★ Adapted for CinemaScope

★ Sound Blimp with Reflex Viewing

Now for the first time—a lightweight camera for CinemaScope photography—the 35mm Camerette with CinemaScope aperture, with full CinemaScope field visible through the reflex viewer. Auxiliary turret and matte for regular photography.

New magnesium alloy blimp with viewing through the taking lens at all times through the Camerette's reflex finder, making a lightweight, fully blimped combination 16mm or 35mm camera. Synchronous motors—110-v single phase, 220 v three phase

ONLY THE CAMERETTE HAS

1. Ability to use both 16mm and 35mm film in one camera.
2. Reflex viewing through the taking lens at all times for both film sizes.
3. Sound blimp with reflex viewing, making a fully blimped, instantly interchangeable 16mm or 35mm camera.



Patents Coutant-Mathet
Manufactured by Eclair, Paris

Write for descriptive literature

BENJAMIN BERG COMPANY

1410 N. VAN NESS AVE. • HOLLYWOOD 28, CALIF. • HOllywood 9-8023

The One-Stop Source Of Supply

The Profitable All-Purpose Film Processor



BRIDGAMATIC JR. 16mm Automatic Reversal Developing Machine—Ideal for TV Stations, Photo Finishers, Industrial or Documentary Producers and Universities.

Bridgamatic JR.
REVERSAL DEVELOPING MACHINE

BRIDGAMATIC JR. REVERSAL assures quality pictures in minutes—Spot news and sports events can be shown **immediately** after they occur. This is the perfect All-Purpose Processor at a price anyone can afford. Reversal speed 1000' per hour—also does negative and positive film. Light-Tight compartment for daylight operation—has 8 stainless steel tanks—completely automatic. Dry to Dry.

MODEL R $1995—Includes basic Bridgamatic features such as overdrive, nylon bearings, air squeegee, built-in drybox, blower, heating elements, 400' enclosed magazine and daylite compartment.

MODEL RA $2495—Same basic features of Model R plus continuously variable speed control, 1200 ft. enclosed magazine, feed in and take up elevators.

TAKE ADVANTAGE OF S.O.S. TIME-PAYMENT PLAN
Trade-Ins Accepted. Send List

Hallen 16mm Recorders

Model 25B—Complete "Lip-Sync" Recording System

- Weighs only 73 lbs., one case, easily portable
- Professional sound stage quality simplicity
- Hallen Drum System has Academy Award winning Davis Flutter suppressor; most stable film motion yet developed
- Simultaneous monitor of recorded track.
- Three inputs—two for microphones and one for music and background
- Standard Motion Picture Research Council 16mm track placement
- High-speed forward and rewind—three separate motors—smooth take up
- Removable Monitor Speaker and power supply
- Licensed under A.T.&T. and W.E. patents

F.O.B. West Coast $1495

Film Numbering Pays Off



The MOY numbers every foot of 16, 17½, 35mm film—simplifies the task of checking titles, footage. Replaces cue marks, perforations, messy crayons, punches, embossing—does not mutilate valuable film. Work prints showing special effects, fades and dissolves require edge numbering to keep count of frames cut or added. Multiple magnetic tracks in CinemaScope stereophonic recordings make edge numbering a MUST. Write for brochure.

With New Improved Non-Clog Inking System $2475

Present MOY owners can easily install the new and improved inking system!

Among Recent Purchasers Are:

Eastman Kodak Co., Rochester
General Film Labs., Hollywood, Cal.
Reeves Soundcraft Sp'alty, Conn.
Holland & Wegman, Buffalo, N.Y.
Amer. Optical (Indel AO), Hollywood
Cons. Film Inds., Ft. Lee, N.J.
Cinerama Productions, New York
Columbia Broadcasting System

Hollywood HFC Synchronizers



2 Gang 35mm **$125**

- Sprockets cut to close tolerances
- Veeder-Root Counters & locking device
- Highest quality precision workmanship
- Built for heavy day in and day out use
- Frame dial
- Cast aluminum machined
- Instant Pad Roller Release

Complete line includes standard and special arrangements for 16mm and 35mm magnetic or optical sprocketed film

"The Department Store of the Motion Picture Industry"

S.O.S. CINEMA SUPPLY CORP.

602 WEST 52nd ST., NEW YORK 19, N.Y.
Phone: PLaza 7-0440 Cable: SOSOUND

EST. 1926

HOLLYWOOD, CALIF. OFFICE—Dept. F, 6331 Hollywood Blvd., HO 7-9202—*For Other Important S.O.S. Offerings See Pg. 543*

ONE OF A SERIES

You might not have noticed it at first glance, but we and this young lady have something in common We both take great pride in our respective abilities to render

SERVICE.

She—as you can plainly see—peels grapes, and if that's what you want, we recommend her unreservedly

If, however, you're interested in film processing, this able young lady will be of no use to you at all For complete 16 mm and 35 mm film services ..magnetic striping any width, any position .. 16 mm color printing, you had better come see us..

DO YOU APPRECIATE SERVICE?...

GENERAL FILM LABORATORIES CORP.
1546 No Argyle/Hollywood 28, Calif /HO 2-6171



A $4500 Value

$2350.00

THE 16MM CAMERA BUILT TO 35MM STANDARDS



A $5300 Value

$2950.00

When the most exacting 35mm professional standards must be achieved in 16mm production, Maurer cameras stand alone as the cinematographer's prime tool. For no other 16mm camera will compare in extreme accuracy of registration and facility of operation.

The Berndt-Maurer camera, with pilot-pin movement for such specialized tasks as animation photography, or the Maurer 05, with "rectangular register" intermittent movement, are both immediately available from Gordon Enterprises.

Like hundreds of other cameras, these Maurer models have been carefully re-manufactured to new standards by skilled technicians in the finest equipped instrument shops in Western America, at Gordon Enterprises. This means that every part, from the smallest to the largest, has been inspected and evaluated by an expert. That is why Gordon Enterprises can say "new-or-better" standards on all equipment it offers. As a prime contractor to the Air Force, the Army and Navy, Gordon Enterprises has repeatedly won commendations for superior performance. Today, motion picture producers throughout the world depend upon Gordon Enterprises for the same superiority in motion picture equipment and for unexcelled service on motion picture equipment.

For these fine Maurer cameras and Maurer accessories, come to Gordon Enterprises. And you'll find hundreds of other cameras, lenses, processing equipment and motion picture production equipment at Gordon Enterprises too, for **Gordon Enterprises has the world's largest inventory of motion picture equipment.**

$2350.00 — Brendt Maurer — 16mm Professional Camera — Type 506-A — Manufactured by J. A. Maurer, Inc.

$2950.00 — Maurer Model 05 — 16mm Professional Camera — Manufactured by J. A. Maurer, Inc.

Cameras are complete with Viewfinder, 3 lenses, sunshade-filter holder, camera carrying case, accessory carrying case, magazine, and choice of 12 volt or 110 volt motor.

gordon enterprises

5362 N. Cahuenga Blvd.
North Hollywood, Calif.

STanley 7-5267
Cable: GORDENT

stancil-hoffman S6 system of magnetic film recording lightweight, standard AC or battery operation 16mm or 17.5mm.

we've packaged a major studio into a portable recording system

STANCIL-HOFFMAN

ECONOMICAL . . . At last, a low cost, completely integrated, PROFESSIONAL magnetic film recording system for studio, portable, or mobile use . . . designed to accommodate any camera and meet your every quality and film recording requirement.

VERSATILE . . . Whatever the power source, camera, or utilization, a simple plug in or interchange of motors is all that's ever required to operate the S6 system. Designed around 24 volt, precisely engineered, Air Force approved batteries. Accommodate 110 or 220 volts, 1 or 3 phase, 50 or 60 cycle power input.

QUALITY . . . Engineered by Stancil-Hoffman, manufacturers of equipment used throughout the world by film producers, radio and television stations, the Military, and nuclear research laboratories. Find out how the S6 magnetic film recording system for portable and fixed recording can best meet your requirements . . . send for specifications now! Credit terms arranged on domestic purchases.

manufacturers of complete recording system
from microphone to release print

STANCIL-HOFFMAN CORP.

921 N. HIGHLAND AVE., HOLLYWOOD 38, CALIF. TEL. HOllywood 4-7461
cable address: STAHHOFF

representatives:

New York & Eastern Seaboard
Electronics Assoc., Inc.
200 5th Street, Stamford, Conn.

East Central Section
Mr. Michael J. Cudahy
5858 Sheridan Rd., Chicago 40, Ill

West Central Section
W. Cozzens
220 Kedzie St., Evanston, Ill

S. W. Caldwell, Ltd.
447 Jarvis Street
Toronto 5, Ontario, Canada

S. O. S. Recording
1545 South Beretania
Honolulu 14, Hawaii

India & Pakistan
Photophone Equipments, Ltd
9, Marine Lines, Bombay, India

ARRIFLEX

New 35 mm Model 2A
With 180° Shutter

A TRULY GREAT CAMERA

for TV, Newsreel and commercial films



For tough and trying assignments, ARRIFLEX 35 is in a class by itself. Reflex focusing through photographing lens while camera is operating—this is just one outstanding ARRIFLEX feature.

Equipped with bright, right-side-up image finder, 6½ x magnification. Solves all parallax problems. 3 lens turret. Variable speed motor built into handle operates from lightweight battery. Tachometer registering from 0 to 50 frames per second. Compact, lightweight for either tripod or hand-held filming. Takes 200' or 400' magazine. Write for free folder.

Blimp now available.
16mm ARRIFLEX also available.

FRANK C. ZUCKER
CAMERA EQUIPMENT CO
1600 BROADWAY NEW YORK CITY

INDUSTRY NEWS

INNOVATION in public relations is practice established by Magnasync Mfg Co., North Hollywood, of loaning company's Thunderbird courtesy car to out-of-town clients Here Magnasync president De J White hands car keys to William A P Smith of Smith System Sound Laboratories, Manila, P I

A new optica method announced by Kodak Research Laboratories will provide faster design of better lenses The first complete analysis of an optical image, a technique that will permit speedier design of better lenses, has been achieved through invention of new mathematical formulas.

The scientific shortcut devised by Kodak's Dr Max Herzberger is essentially a way of analyzing the optical image and considering it as a superimposition of five simple types of images He accomplished this by finding five simple types of image errors, from which he can synthesize the most complex optical image

Until now, lens designers, using computing machines, have laboriously traced rays of light through a lens system during the design stage. This has been reduced to the tracing of only nine rays which, by projection with Herzberger's mathematics, is equivalent to tracing perhaps 1,000 rays

* * *

Invention of an electronic device to permit accurate scene counting during inspection screening of either 16mm or 35mm film, is announced by Consolidated Film Industries. Method was developed by Ted Hirsch and is being patented by CFI.

During printing, the clear edge side of the film is purposely fogged where scene changes are indicated, causing a thin, black mark to appear at the beginning of each scene. A photo-electric scanner, mounted on the projector for this purpose, scans the clear edge while the print is being screened. As each fogged strip passes the scanner, the accompanying scene-change is recorded in full view on an illuminated counting device located below the screen in the projection room.

Thus CFI technicians and customers can identify every scene by number in order to record on-the-spot suggestions for correcting subsequent re-printing.

* * *

A unique new 30-minute educational film that shows revolutionary new methods of achieving labor-saving technique in producing animated films, was screened publicly for the first time at the studios of United Productions of America, Burbank, August 24th

Film was produced by Animation Equipment Corp., New Rochelle, N. Y., manufacturers of Oxberry animation and camera equipment It demonstrates zooms, pans, dissolves, wipes, pop ons, cutouts, and multiplane procedures and shows how high quality animated productions are made in less time and at less cost through use of motorized animation stands and tables.

The film is scheduled to be shown before groups in other film production centers in the U. S during the coming months.

* * *

In his firm's annual report, just released, James Barker, young president of Capital Film Laboratories, Washington, D C., points out that since World War II the number of 16mm projectors in use has increased ten-fold from about 50,000 to some half a million, and that the number of "general interest" films available in 16mm increased over fifty-fold in just the first seven years after the war ended.

Jim Barker

Today, the report adds, the footage of 16mm film exposed for professional use each year runs into the millions of feet, and rivals the film consumption of the theatrical film field.

Capital is one of the leading eastern laboratories servicing the 16mm film industry. It is one of the only three lessees of the Scotchtrack brand magnetic laminate process perfected by the Minnesota Mining & Mfg. Co.

WORTH
WAITING FOR

ARRIFLEX 16®

The World's Outstanding 16mm Camera

Because it has so much more to offer, the Arriflex 16 has become the most wanted 16mm camera in the field. The demand has been greater than the supply from the very beginning . . . and for the best reasons in the world:

- The Arriflex 16 is the only 16mm camera with a mirror-reflex shutter for continuous thru-the-lens focusing and viewing—even during actual shooting. There is no beam-splitting and no light loss; no parallax and no need for extra finders.
- It is equipped with registration pin assuring absolute frame registration and rock-steady pictures.
- A built-in electric motor drive permits uninterrupted filming—no need to stop and wind a spring.
- By employing a diverging turret, 3 lenses from extreme wide-angle to 300mm telephoto can be simultaneously mounted—without physical or optical interference.

There are a host of other features that equip the Arriflex 16 for every possible type of professional filming: Footage and Frame Counters—Tachometer—Detachable Matte Box—400 ft. Accessory Magazine, etc. Its extreme compactness and light weight (only 7½ lbs. with Matte Box) makes it also ideally suited for hand-held shooting.

The quality, performance, and exclusive features of the Arriflex 16 have created a great demand for this camera. To assure earliest possible delivery, we strongly urge you to place your order now. And even though there is some delay, remember . . . the Arriflex 16 is worth waiting for.

ARRI

For complete information concerning Arriflex 16mm and 35mm cameras, and Arri film lab equipment, write to

KLING PHOTO CORP. • 235 Fourth Ave., New York 3, N. Y. • 7303 Melrose Ave., Los Angeles 46, Calif.



need location lighting . . . fast?

Call an Jack Frost, one of the nation's largest suppliers of temporary lighting facilities.

Wherever you are, whatever your lighting needs, you can depend on Jack Frost's expert handling and complete range af equipment, from a 100 watt inkie to 225 amp arc with mobile power plants. In the studia too, we can supplement your present equipment to meet any situation, anywhere. We've been doing it for years for many af the top shaws.

Our service includes complete installation and removal at one low cost.

free estimates

Write ar wire for a free estimate and a Free Catalag af Equipment.

JACK A. FROST

Dept. AMCI

234 Piquette Ave., Detrait 2, Michigan

425 Burnamtharpe Road, Taronto 18, Ontario

WE PROUDLY PRESENT . . . . another CAMART PRODUCT!

THE DUAL READER

Patent Pending

Price: $195.00
(LESS VIEWER)

The DUAL READER will:

- Play SOUND film with ANY 16mm motion picture viewer
- Edit SOUND and PICTURE in perfect synchronization.
- For SINGLE and DOUBLE system editing
- Works with left to right and right to left viewers.
- Operates on 110-120 volts, 60 cycles, AC.
- Includes sound head, amplifier, and base for viewer.
- Smart modern design, attractive brown wrinkle finish.

SOUND HEAD
- Optical slit, pre-focused exciter lamp socket.
- Reads variable area or variable density track.
- Highly polished chrome plated film track
- Will not scratch or damage your film.

AMPLIFIER
- 5 watt output with built-in Alnico speaker.
- Exciter lamp rheostat control for hi-fi sound.
- Speaker can be moved away from the editing table
- Headphone jack for listening without disturbing others.

SEND FOR DESCRIPTIVE LITERATURE!

AND DON'T FORGET OUR OTHER CAMART PRODUCTS

- Boom arm Dolly • Baby Dolly • TV Mike Boom
- Tightwind Adapter • Optical FX Unit • Rotator Lens
- Triangles • Car-top Clamps • Slate & Clapstick
- Electric film timers • Synchro-view-lite
- Scout Tripod • Baby Cub Tripod • Hi-hat

• • • • •

- Fully equipped modern machine shop to design and build experimental and special equipment.

• • • • •

- Moviolas serviced, repaired, and rebuilt
- Authorized Bell and Howell repair station.

SALES REPRESENTATIVES

- Auricon Super-1200 and new Pro-600 cameras.
- Arriflex 16-35mm reflex cameras and blimps.
- Used Mitchell, Maurer, Bell & Howell cameras.
- Bausch & Lomb BALTAR lenses mounted for
- Arriflex and other cameras.
- Bardwell-McAlister Colortran REGEL LIGHTS
- New CONE LITES perfect for color.
- Magnetic recording equipment and microphones.
- Moviola film editing machines.
- Neumade editing supplies and equipment.
- Bodde background slide projectors and screens.
- Printers, processors, and lab equipment.

THE CAMERA • MART INC.

MOTION PICTURE AND TELEVISION EQUIPMENT

1845 BROADWAY at 60th STREET
NEW YORK 23, NEW YORK

PHONE: CIRCLE 6-0930
CABLE: CAMERAMART

THE CINE-SPECIAL camera, shown here in the hands of naturalist-photographer Dr. Olin S. Pettingil, Jr., makes it possible to shoot pictures of fast action at shutter speeds as high as 1/560 second

BELOW is dial of Norwood Director exposure meter showing comparative positions of shutter openings with cine frames figures. Author suggests readers memorize these comparative positions as they cannot be readily marked on the meter dial itself



Fig. 1

Exposure Determination For Variable Shutter Speeds

By FRANK P. FRITZ

PROBLEM-EXTREME SLOW MOTION - HI-SPEED ACTION AT FASTER SHUTTER SPEEDS

CINE CAMERAS having variable shutters, such as the Eastman Kodak Cine-Special and Pellegrini-modified 8mm and 16mm Bolexes, offer advantages beyond the ability to make fades and lap-dissolves. Such cameras can be used to modify exposures without altering lens aperture for certain photographic effects or results. For example, where you want to pan from bright sun to shade and at the same time maintain full and equal exposure in both areas, the proper exposure can be sustained during the panning operation by changing the variable shutter opening as the camera moves. This method is superior to that of progressively changing lens aperture because with the latter, the depth of field is altered.

This technique poses the problem of determining the correct f/ stop for the different positions of the variable shutter. To understand more clearly the method of using an exposure meter for aperture determination for the variable shutter, it should be remembered that most cinema cameras provide only one shutter speed, although they may offer a range of different *camera* speeds such as 8, 16, 24, and 32 frames per second, etc. Thus, in certain cases, exposure time can be modified by changing the camera speed, but this method is not always desirable.

Briefly, the advantages offered by the variable shutter are:

—Ability to make fades and lap dissolves in the camera.

(Continued on Page 540)



Fig. 2

DIAGRAMS show how meter is used to determine correct shutter opening when photographing fast action at 64 fps. Normal exposure for 64 fps is determined as f/4 (2). Shutter speed dial is rotated to bring the fps figure 16 over the f/4 figure (3). This position on the meter is still 64 fps with variable shutter open. Now, under the 64 fps-¼-open marks is indicated the aperture to use, i.e., f/2 (4).

MAGNASYNC
SYNCHRONOUS
Magnetic Film Recorders

Magnaphonic
SOUND SYSTEM

Producers!

Bring dubbing costs DOWN and CONTROL sound quality

with Magnasync X-400 Type 13 dubbers

As significant as the tremendous savings made possible by Magnasync magnetic film recording is the degree of **quality control** which it affords the exacting producer. In mixing, dubbing and transfer work the Magnasync X-400 permits you a degree of perfection which you can achieve consistently by doing the work yourself.

SOUND EFFECTS edited to fit the script with blank leader stock between split-second synchronized effects (Loop rack attachment available).

MUSIC TRACK scored to packaged picture. Music can be rescored without affecting other portions of the master track.

DIALOGUE TRACK recorded on location in "Lip-Sync" or narrated to fit picture.

PLUG-IN PREAMPLIFIERS mounted on rack panel cradle. Power switch, Fuse and Pilot light on front of panel. Zero level, 600 ohm, balanced line output.



INDIVIDUAL DRIVE MOTORS with positive gear interlock assure absolute sync from dead start. Separate synchronous drive motors operate each dubber is independently to assure optimum motion stability.

Send for complete specifications, prices and delivery schedule

DEALERS

NEW YORK—Camera Equipment Co., 1600 Broadway, New York 19. JUdson 6-1420. Cable Address CINEQUIP.

CHICAGO—Zenith Cinema Service, Inc., 3252 Foster Ave., Chicago 25, Ill. IRving 8-2164.

SAN FRANCISCO—Brooks Camera Co., 45 Kearney St., San Francisco, Calif. EXbrook 2-7348.

CANADA—Alex L. Clark, Ltd., 3745 Bloor St., Toronto 18, Ontario. BElmont 1-3303.

AMERICA'S LEADING MANUFACTURER OF MAGNETIC FILM RECORDING AND REPRODUCING DEVICES

MAGNASYNC MANUFACTURING CO., LTD. • 5521 SATSUMA AVE., NORTH HOLLYWOOD, CALIF. • POplar 6-1692

Make-up Magic For Today's Color Films

Recognizing the varied problems pased by the new calor emulsians, American Cinematographer calls upon Hallywood's tapmost make-up authority for answers.

By WALTER RAMSEY

"WHEN FACES TURN RED, green or blue in this age of color photography, we must suspect more than high emotions or extreme low temperatures," said Max Factor, Hollywood make-up authority. "Actually, these results come from a combination of make-up, lighting and film used without true color knowledge and coordination."

How to keep up with make-up and color compensation for the new, ever-changing color films, both 16mm and 35mm, is a problem faced by all those who are interested in the film industry in every way. Here, in an exclusive interview for *American Cinematographer*, Max Factor, Jr., recognized expert in the field of motion picture make-up, gives the answers to these problems in simple, easy-to-understand terms and reveals the correct make-up methods and colors which should be used for the various new color negatives. Nor is the information gleaned by mere chance, but results from Mr Factor's years of careful research and close cooperation with all leading film companies

"With the constant development of new color emulsions," continued Factor, "improved make-up colors must be devised which will produce the most natural results. The make-up problems encountered in color motion picture photography are more numerous than in black-and-white photography. Color temperature of light, light intensity and, of course, the developing process itself, directly affect the colors of the make-up."

When selecting colors of make-up, one must be familiar with the particular negative stock being used, as each type of film calls for a different solution to compensate for its unique properties. But it is not necessary to guess or experiment; accompaning this article, you will find several charts furnished by the Max Factor Make-up Studios, indicating the suggested make up for all types of color film in current use.

"In Ansco color, Technicolor and Eastman Color No. 5248," Factor continued, "the reds become highly intensified in the developing of the film. Therefore, a true red lip rouge will reproduce unnaturally and the result will be undesirable. Pastel pinks and pink-orange tones are used, in these cases, for both cheek and lip rouge. These colors will reproduce natural blush tones on the cheeks and natural red on the lips. With Kodachrome film, however, the cheek and lip rouge colors applied will be faithfully reproduced in the final print; so for this film, darker reds are used than for Technicolor, Ansco or Eastman 5248.

"Another important aspect of make-up for color photography today is the reproduction of natural complexion tones on both men and women. Selecting the proper shade for each individual is the secret to obtaining the most natural results. For example, the standard shade of our Pan-Stik for women is 626B for Technicolor film. But should a particular actress have an extremely ruddy complexion the next shade darker would be more effective: the darker color would conceal the very ruddy tone of the skin and at the same time prevent the skin tone from becoming too light.

"At this point," Factor went on, "special make-up effects must be considered. A color which is correct for a normal complexion tone would not give the desired effect if, for example, a caucasian were to portray an oriental. A special color should be selected to obtain the desired result; a color that would not incorporate reds, and one that would reflect a minimum of blue. The color blue is mentioned in particular because it is the hue which Eastman Color negative favors. Of course a great deal of color correction is possible in processing, but only to a certain point," Factor warned. "Too much blue in the foundation color results in a muddy complexion tone, and the presence of too much blue will cause the lips to appear a purple color."

The question most asked Max Factor is: What is the difference in the make-up colors now used and the colors used several years ago? His answer is that the major difference is to be found in the new color pigments which have been discovered after months of research in their laboratories. These new color pigments made new methods of refining

CORRECT METHOD of applying lipstick for motion picture make-up is demonstrated here by Hal King, director of make-up for Max Factor, Hollywood. Model is Lita Baron.

MODEL removing all her make-up. Note how face is without expression, eyes are dull, lips indistinct

SAME MODEL with properly applied motion picture make-up, resulting in glamorous appearance—and a decided transformation.

SAME MODEL with different make-up and blonde hair—with the make-up properly chosen to harmonize with the latter.

possible. This has resulted in colors with more light-reflective qualities than ever before. The colors today are very clear, very clean, ranging from soft light-amber-pink through the tan tones, with each of the colors having a delicate rosy undertone.

"Consider, too, the color of make-up foundations from the viewpoint of color balance between the man and the woman. If the woman is made up extremely light and the man very dark, on the screen the variance in complexion tones will be so obvious as to be disconcerting to the viewer. Selection of foundation colors which are closer together in depth will give a better balance to the skin tones of the man and woman. The average director of photography is well aware of this, because it is most difficult to light two people with extreme divergence in complexion tones."

TO CREATE a clear, satin-smooth complexion tone, pancake make-up should be applied with a soft sponge

"What about the technique of make-up application?" we asked Mr. Factor.

"Make-up, incorrectly applied, will destroy the perfect effect you wish to achieve," he said, "even though the proper selection of colors has been made. Never apply foundations so heavily as to completely conceal the texture of the natural skin. A heavy application of foundation will result in a mask like appearance. High-lights and shadows, used to correct facial proportions, must be blended very delicately so that each color fades naturally into the foundation color. Usually, a color two shades lighter than the foundation is sufficient for a highlight; and for shadows, a color two shades darker. A fine natural sponge or a flat sable brush are better appliances to use for blending purposes than the finger-tips.

"Cheek rouge, as we have said, must be pastel in hue and it must never contain blue. It is always blended to a soft blush tone for current films. Eyebrows should be pencilled with tiny hair-like strokes to simulate the real eyebrow hair. A solid, continuous line should never be used. Perfection in make-up application is the rule to be particularly followed here.

"Because blue is a problem with most color negatives, but especially with Eastman, blue eyeshadow is not used except for certain special effects. A gray or brown eyeshadow, or a combination of the two, is used today. These colors will give a natural eyeshadow effect. The application must be very delicate, and the edges blended until the color fades away.

"Women's eyes may be made to appear larger by outlining the eye with an eyebrow pencil. The color brown is almost always used and the line is blended to a shadow. The line must be drawn as close to the base of the eyelashes as possible. This will give the desired effect and, too, will serve to prevent the eyes from appearing red-rimmed due to light glare or fatigue.

"Eyelash make-up is a *must* for all women appearing before the camera and false lashes may be worn where indicated. These lashes are always trimmed and shaped to give a natural effect.

"Lip rouge is best applied with a lip brush. In this manner a perfectly sharp outline is achieved, giving a clean, shaped lip-line without a feather edge. Lip rouge should be blotted with tissue at least once after applying to the lips,

(Continued on Next Page)

LINE, pencilled on upper and lower lids and blended to almost a shadow, prevents eyes appearing red-rimmed, makes eyes larger.

THE PERFECT lip line is best achieved by using a lip brush made for the purpose. Careful outlining here is important.

for the most natural effect. For a more dramatic effect, we suggest a heavier application of rouge and no blotting for a high stay-on lustre.

"Even the powder used in modern color make-up has changed," Factor continued. "In the past, as you may recall, there was a definite added color to the powder. With current color films, this former color in powder is not only unnecessary, it is taboo. Once the foundation color is carefully selected, it must *remain*; the modern powder is therefore translucent, and adds no color to the foundation whatsoever."

Mr. Factor concluded his remarks by emphasizing the usual care required in applying make-up to the neck, shoulders, hands and arms (if exposed) to give a continuity of skin tone. If the hands, for example, are left in their natural coloring while the face, arms, shoulders and neck are made-up, the subject will often appear to have red, blue or even white hands. Continuity of make-up is a paramount consideration.

Costume colors should be carefully considered when choosing the proper lipstick shade. If a woman is wearing a fuschia gown and an orange-colored lip rouge, the color-clash is obvious and far from beautiful. Lipstick does not necessarily have to match the costume, but it should *harmonize*, Factor warned. Often, a red-toned gown is so dark that the same shade of lipstick would be out of line with the film demands as outlined in the charts.

Films are constantly changing and being improved. Make-up especially designed for last year's negative films may not be adequate for the new emulsions discovered in recent months. However,

(Continued on Page 544)

SUGGESTED MAKE-UP CHART FOR EASTMAN COLOR FILM NO. 5248

	WOMEN	MEN
Pan-Cake or Pan-Stik	7-25A or 7-25B or 7-25C	VC-7 or 7-25G or 7-25H
Powder	C3 238 (Translucent)	C-3 238 (Translucent)
Creme Cheek Rouge	Flame or 1B Lip Pomade	
Dry Rouge	Flame or Light Tech.	Dark Tech. (Sparingly)
Moist Rouge (Lips)		T-3 (Sparingly)
Lip Pomade (Lips)	7-22	
Eyeshadow (Liner)	Brown #3 or Blue-Grey #6	Brown #3
Eyebrow Pencil	Lt. Brown, Brown, Black	Brown or Black
Eyelash Make-Up	Brown, Brownish-Black, Black	Brown (Optional)

VC Series of Pan-Cake and Pan-Stick: VC1, VC2, VC3, VC4, VC5, VC6, VC7, VC7A, VC8, VC8A, VC9A
7-25 Series of Pan-Stick: 7-25, 7-25A, 7-25B, 7-25C, 7-25D, 7-25E, 7-25F, 7-25G, 7-25H
7-25 Series of Pan-Cake: 7-25A, 7-25B, 7-25C, 7-25D, 7-25E, 7-25F, 7-25G, 7-25H
The VC Series of Pan-Stik and Pan-Cake are the original series made for Eastman film. The 7-25 Series of Pan-Stik and Pan Cake are the latest series and contain Pink undertones. Either series is correct to use. The preference is the individuals.
7-22 Lip Pomade is lighter and more natural appearing than 7-16.
7-16 Lip Pomade reproduces a deeper red tone.

SUGGESTED MAKE-UP CHART FOR ANSCO COLOR

	WOMEN	MEN
Pan-Cake or Pan-Stik Make-up	VC5	VC8
Powder	Tech. Special	Tech. Special
Creme Rouge (Cheeks)	Flame	None
Dry Rouge	Flame or Light Tech.	Dark Tech.
Lip Pomade	1C	
Moist Rouge (Lips)		T-3
Eyeshadow (Liner)	Brown #3 or Blue Grey #6	Brown #3
Eyebrow Pencil	Lt. Brown, Brown, Black	Brown, Black
Eyelash Make-Up	Brown, Brownish-Black, Black	Brownish-Black (Optional)

VC Series of Pan-Cake and Pan-Stik: VC1, VC2, VC3, VC4, VC5, VC6, VC7, VC8, VC8A, VC9A
VC1 is the lightest shade. The colors become progressively darker until they reach 9A which is a very deep tan.
Colors lighter or darker than VC5 may be used for lighter or darker skin tone effects, for women.
Colors lighter or darker than VC8 may be used for lighter or darker skin tone effects, for men.
Lip Pomade 7-16 may be used for a pastel lip color effect on the lips of women.
Women whose complexion tones are quite ruddy should wear 626B or 626C Pan-Cake or Pan-Stik, instead of VC5. These colors contain less red pigment.
More neutral skin tones for men who are very ruddy are K1 and K2 Pan-Cake or Pan-Stik.

EASTMAN

PROFESSIONAL

MOTION PICTURE

FILMS

W. J. GERMAN, Inc.

John Street
Fort Lee, New Jersey

6040 N. Pulaski Road
Chicago 30, Illinois

6677 Santa Monica Blvd.
Hollywood 38, California

THIS IS JUST THE BEGINNING OF 16 MM!



Talk was that other film sizes than 16mm could do better jobs in the industrial, educational and commercial fields.

Not while there is a film laboratory like Precision, bringing 16mm to the peak of perfection. In fact, we are demonstrating daily that 16mm can do more—and better—things in movies than have been done before.

Precision Film Laboratories developed unique equipment to realize the fullest potentialities in 16mm, such as the optical track printer; timing, fades, dissolves, scene-to-scene color corrections, invisible splicing without notching originals; direct electric printing and many others.

No, 16mm is just beginning. Depend on it for your next film project and, of course, depend on Precision to do exactly the right job in bringing life and sparkle to the best of your production efforts.

you'll see and hear

PRECISION

FILM LABORATORIES, INC.
21 West 45th Street, New York 36, New York

A DIVISION OF J. A. MAURER INC.

In everything, there is one best . . . in film processing, it's Precision

Pre-printing Preparation Of 16mm Films

Recommendations aimed at standardizing preparation and marking of negatives and work print for better results offered by the Association of Cinema Laboratories, Inc.



FIG. 1—Top and center diagrams illustrate "checkerboard technique" of making splices invisible when preparing 16mm A & B rolls for the laboratory. Bottom diagram shows the recommended method for preparing A & B rolls for dissolves

THE ASSOCIATION of Cinema Laboratories, Inc., this month began the distribution of three bulletins containing the Association's recommendations to producers of 16mm motion pictures for the preparation of A & B rolls, the preparation of 16mm printing leaders, and method of marking work prints to indicate effects. It is the first concerted effort by the industry's leading film laboratories to secure the cooperation of film makers towards standardizing their methods on pre-print preparation of films.

In the preparation of original 16mm A & B rolls, there are ten specific recommendations:

Black Leader: It is recommended that only black leader be used between scenes and that such leader be fully opaque. This leader can be made by fully exposing a length of positive film and developing it in a positive bath. If black leader is old, it is advisable to check it for shrinkage. Black leader should be used for *negative* A & B rolls also.

Double or Single Perforated Leaders: It is the Association's recommendation that only double-perforated leader be used when all the original is double-perforated. When some or all of the original is single-perforated, the use of single-perforated black leader is recommended to prevent possible future damage to the original. The perforations in the black leader should, of course, be on the same edge of the film as those in the original.

Invisible Splices: In order to make 16mm splices invisible on the screen, it is recommended that the A & B rolls be prepared using the "checker board" technique. (See Fig 1). This technique is accomplished by alternating the scenes back and forth on the A & B rolls. The splices should be made in a splicer that makes one of the cuts on the frame line and the other cut in the picture area. When splicing the scene to black leader, the scene should be placed in the splicer in such a manner that the scraped portion and visible cut of the splice occur only in the black leader. After splicing the head of the scene in this manner, in order to correctly make the splice at the "tail" of the scene, it will be necessary to turn the scene around in the splicer.

It is further recommended, however, that the producer consult his laboratory before preparing A & B rolls because some laboratories request that a number of extra frames be left on the head and tail of each scene in matching.

Fades: When a fadeout is followed by a fadein, it is recommended that the fadein scene be carried across to the other roll without any overlap. The procedure is the same as that followed in preparing for "invisible" splices. Instructions must be given so that the fades will be printed in at the desired places.

(Continued on Page 544)



FIG. 2—Method and symbols for marking work prints for guidance of laboratory technicians in making special effects

COMBINATION of graceful vapor trails of B-36 and vast sea of clouds boiling up from the earth below presented rare sight for cameramen

WHILE most everyone is familiar with sight of fleet, high-flying B-36 from ground, these shots afford rare bird's eye view from 8-mile height

Photography At 40,000 Feet

How the spectacular aerial sequences for "Strategic Air Command" were planned and photographed.

By WILLIAM DANIELS, A.S.C.

Director of Photography, "Strategic Air Command"

THE BIRD'S-EYE VIEW of giant, vapor-trailing B-36's in flight at 40,000 feet, backdropped by the most beautiful cloud displays seen anywhere, have prompted many who have seen Paramount Pictures' "Strategic Air Command" to inquire how these aerial shots were photographed.

The production is the first large-scale, outdoor film photographed in VistaVision and color. It is also the first motion picture affording the public rare and breath-taking aerial views of the Air Force's B-36 planes in flight.

Photographing aerial sequences such as appear in "Strategic Air Command" required something more than simply taking a camera up in a plane and shooting. First, the planes are in almost daily use in training personnel for SAC. The Strategic Air Force is the atom-bomb carrying command whose intercontinental bombers provide the retaliatory strength upon which the U.S. relies to keep the peace. Unlike when shooting on the studio lot or on other locations, it wasn't simply a matter of checking the weather of a morning and—finding

Wm. Daniels

Tom Tutwiler

it photographically ideal—deciding: "We'll make those air shots today." No, we had to give the Air Force 24 hours notice whenever we wished to shoot scenes involving planes. And before each aerial filming session was begun, a four-hour pre-flight briefing of Air Force personnel taking part and of our production technicians was standard procedure. In short, we of the studio had to adjust our working procedure in harmony with operations of the SAC.

Long before a camera turned—even before cinematographer Tom Tutwiler, A.S.C., knew he had been elected to do the aerial photography of this picture—Director Anthony Mann, Art Director Earl Hedrick, Production Manager Curtis Mick, and I journeyed to MacDill Air Force Base in Florida, to Carswell AFB, Ft. Worth, Texas, and to March AFB near Riverside, California. At each location we discussed the script action for the aerial sequences with SAC and AF officers and made a survey of the planes that were to be made available to us for much of the aerial photography.

Never before had studio cameras been used in these planes for photography of any kind. It was very important therefore to make use of the opportunity to plan the camera locations—the positions in the planes where the cameras were to be mounted— and more important, to plan the special camera mounts that would be required. In the B-36 we needed an opening (window or port) through which to shoot at a downward angle while the plane is in flight. The bomb sight port protected by heavy optical glass proved a natural for this; a great deal of Tom Tutwiler's spectacular aerial shots were made with the VistaVision camera mounted in this position.



JUST kissing the cloud tops is this SAC B-36 laying down its vapor trails at an altitude of over 40,000 feet.

TOM TUTWILER, ASC, shooting from another B-36 with a VistaVision camera, captured these rare shots for "Strategic Air Command"

To shoot from this type plane alone, I had to design four different camera mounts: for the B 36 nose, the forward "bubble" or gun port, and two for the aft gun ports.

On our return to the studio from the survey of the Air Force bases, detailed specifications for building the various camera mounts were turned over to the studio's camera department. In the meantime, we had arranged with Paul Mantz to supply his famed B-25 camera plane for our use in making some of the aerial shots.

This assignment marked the first time that the Mantz camera plane had ever been used for VistaVision photography. It was therefore necessary to completely alter the camera mounts in both the nose and the tail to accommodate the Vista Vision cameras. Mantz's ship was used in filming all aerial shots that did not require going to extreme altitudes. When it was necessary to shoot from heights of around eight miles and travel at near sonic speeds, one of the Air Force's jet aircraft was used as a camera plane. It was such a plane that Tom Tutwiler used in shooting the rare, unearthly panoramic shots at 40,000 feet that highlight the climax of the picture.

Altogether, the aircraft used in the action or the photography of "Strategic Air Command" included the aforementioned B 36s, the Mantz B-25 camera plane, B-47 bombers, H-19 helicopters, KC-97 in air refueling ships, T-33 jets, C-97s and C-124 Globemasters. The helicopter was also used as a camera plane for special shots.

This cooperation and permission to shoot SAC in actual operation was extended us by the Air Force because it was felt the film could be a definite contribution to national security. Furthermore, the special type of mature individual SAC requires for personnel is not easy to find. The film illustrates the type of temperament a man must possess to be eligible for duty in SAC.

Col. O. F. Lassiter, one of the nation's most renowned pilots, was given leave from his duty as Director of Operations, 12th Air Division, March Field, to act as technical advisor and liaison officer with

(Continued on Page 547)



PAUL MANTZ's famed camera plane was used by cameraman Tutwiler to shoot a great many scenes for "Strategic Air Command." Photo shows nose mounting VistaVision cameras

TAIL OF SAME plane, showing canopy removed from the aft camera position. It was necessary to modify the camera mounts in both nose and tail in order to accommodate VistaVision cameras

ALFRED MILOTTE, in the special armored 4-wheel-drive camera car, photographs a mother lion bringing home the entre for her cubs' dinner. Elma Milotte, in a Jeep some distance away, made this shot with a telephoto lens. In background is famed Mt. Kilimanjaro.

Filming "The African Lion"

Alfred and Elma Milotte's three-year camera safari for Walt Disney's latest True-Life Adventure feature carried them for more than 50,000 miles through the primitive lands of Kenya, Tanganyika and Uganda.

TO BRING THE FIRST full accurate life story of the King and Queen of Beasts out of the African wilderness for movie audiences, Alfred and Elma Milotte, famous team of 16mm cinematographers, literally consorted with lions for many months in photographing Walt Disney's newest True-life Adventure feature, "The African Lion."

In their 32-month camera safari for the Disney assignment the Milottes lived as closely amongst groups of lions as they ever have with human neighbors. In that time, traveling in a truck which was both home, laboratory and camera car, they traversed the vast Serengeti plain and contiguous animal territory from Mt. Kenya to the lofty, storied Mt. Kilimanjaro.

Here they photographed the greatest pageant of wildlife anywhere on earth, uncountable in numbers, on over 100,000 feet of 16mm Kodachrome film, including in the lion's domain elephant, rhino, giraffe, leopard and cheetah, zebra and wildebeest, baboon, hyena, jackal and wild dog packs, scores of antelope and gazelle species and birds of many feather.

The real preparation for the safari began with the construction by Disney engineers of the mobile carrier which was to transport the Milottes and their equipment into and through the rugged African interior, and which was to serve as a combination home, transport, and mobile camera car. On the chassis of a new 4-wheel-drive truck, a sturdy, steel-sheathed cabin was erected. This provided two pullman bunks, lockers for clothing, cameras and camera equipment; and a collapsible steel parallel or tower on top for use in gaining higher vantage point for the cameras. Heavy optical glass protected the windows and camera ports of the cab.

The Milotte's motion picture equipment consisted of a 16mm Arriflex camera, two Cine Specials, and a Filmo Special equipped with a detachable 400-foot film magazine. The wide array of camera lenses ranged from wide-angle up to 16 inch telephotos. Three exposure meters insured them against the contingencies of loss or unexpected damage that invariable occur when only a single meter is carried.

While a substantial quantity of 16mm Kodachrome film—both Commercial and Regular—was taken along, the stock was replenished at intervals by shipments from Disney headquarters, which the Milottes picked up at Nairobi, base of operations. At the same time, exposed film was shipped via air-mail to Hollywood for processing. The processed film was then sent to Disney studios. Not a foot of it was seen by the Milottes until they returned to Hollywood some thirty months later.

Actually, there would be no advantage for the Milottes in seeing what might be termed "dailies" or "rushes." For if a shot was marred by poor exposure or focus or framing, which it rarely was, there would be nothing they could do about it anyway, it couldn't be restaged and shot. So the policy was to shoot on the basis of long experience in photographing wild life, to photograph enough of it and thereby provide more than enough footage for the production as planned.

We use the term "planned" loosely here, for actually there was no shooting script; no list of subject material supplied to the Milottes. When they set out on the vast African plain, they were on their own to shoot what they could, when and wherever they could find it—based, of course, on a knowledge gained through many years experience in wild life photography and a study of books on Africa and its denizens of the bush. In addition, the Milottes received unlimited cooperation from officials of the Royal National Parks of Kenya, the Serengeti National Park of Tanganyika, Queen Elizabeth National Park of Uganda, Kruger National Park of South Africa, and the Game Departments of Kenya, Uganda and Tangayika.

During their twenty years of wildlife photography, from arctic to equator in many lands, Alfred and Elma Milotte have learned how to behave and how to command respect in the presence of wild creatures. After proving they meant no harm, the human intruders were accepted as just another kind of animal. Their steel-clad camera truck became a familiar feature of the landscape. As long as the Milottes kept their tolerated distance, the lion families went on about their business of life and death in the melee of survival passions to which they were born.

Making their camera setups confi-

WILD ANIMAL view of the Milottes—Al behind the Arriflex 16 and Elma ready with her reflex 35mm still camera. The big telephoto lenses seen here were used in making the majority of shots from the camera car, which also served as home for filmers.

dently, yet cautiously, often within less than 100 yards of a subject in action—outside as well as inside their truck—they filmed the whole gamut of leonine behavior through courtship, hunt and kill, family affections, maternal discipline and the jealous outbursts in the harem of half a dozen or more females.

Much of the success of the Milottes' photography is based on a routine procedure which they invariably follow in entering a new region. Before ever thinking of readying their cameras for shooting, they first spend a period of time exploring the region and studying it—its accessibility, the light conditions, the pictorial values of certain features of the terrain, etc. Here, as in no other place, they found excessive heat one of their chief problems. The great heat waves resulting from the intense midday sun so distorted distant images that photography in mid-day was impractical. For this reason, most of their shooting occurred during early morning and late afternoon.

The pre-shooting surveys of the Milottes included careful observation of the animals they planned to film—their eating habits, migration patterns and indicies of mating seasons. Here the Parks officials were of inestimable help in providing valuable information.

Much of the success of their wildlife photography is based on the fact both Al and Elma have studied wildlife habits extensively, and when on a filming assignment they automatically think like the wild creatures on which they train their cameras. For example, while on the Serengeti plains, they were watching a group of lions and planning their next sequence of shots. Al observed one lioness suddenly stretch, yawn and get to her feet. "She's going over to the water hole!" he told his wife. They started the truck and sped to the waterhole. Within minutes, the lioness put in an appearance, just as Al had predicted. By now,

(Continued on Page 542)



LIONS give the Milotte camera car careful inspection, affording Al at camera at left opportunity to get some interesting closeups of lions in action on the Serengeti plains of east central Africa.

All photos copyrighted by Walt Disney Productions.

THIS BATTERY of movie and still cameras, lenses, film magazines and exposure meters is the photographic gear used by Alfred and Elma Milotte on their African safari for the Disney True-Life Adventure feature, "The African Lion."

THE THREE units pictured above comprise the new Stancil-Hoffman S6 portable magnetic film recording system. Above is remote microphone preamplifier with push-button announce microphone for scene number identification, plus many other unique features.

FILM TRANSPORT of the S6 system. Recording and playback heads are located beneath decorative cover in center. Dual-flywheels insure balanced mechanical filter system for velvet-smooth film travel. Footage counter with reset knob is at bottom left.

Innovations Highlight New S6 Magnetic Recorder

Stancil-Hoffman Carp. has packaged the complete facilities af a major studia sound recarding system in a lightweight, portable, 3-unit magnetic film recorder.

By FREDERICK FOSTER

THREE, PORTABLE, easy-to-carry pieces of equipment comprise the new model S6 Stancil Hoffman professional magnetic film recording system. The three unit package has been especially designed for three-way use—for studio, portable or mobile recording. Whatever the power source, camera, or utilization, a simple plug-in or interchange of motors is all that is ever required to operate the S6 recorder. Designed around 24-volt. precisely engineered. Air Force-designed batteries, the system also operates on 110 or 220 volts, single or three phase 50 or 60 cycle power input.

The immediate and obvious requirements as to size and weight have been successfully met without any compromise in performance. Particular care has been taken in the design and fabrication of the large cross-sectional castings and the bearing suspension along with the weight distribution of the mechanical members.

The aim for high efficiency and low power consumption is seen in the design which uses batteries for power. This was accomplished by designing the amplifiers for D.C. operation. Every moving component of the recorder is mounted on precision ball-bearings, carefully aligned and assembled. Many of the frills are eliminated to conserve both power and maintenance time.

The S6 uses a single motor drive, which operates a worm gear reduction for the main sprocket drive as well as the take-up clutch. By carefully lapping a metal worm gear working in conjunction with a nylon gear, a low-flutter drive system has been obtained. The mechanical filter is a balanced system consisting of two flywheels and two spring-loaded stabilizer arms using a silicone dashpot on one of the members. While the weight of the flywheels has been kept to a minimum, the system presents extremely low flutter in the order of .15% to .2%.

For simplicity in threading, a single sprocket is used plus an automatic control to open and close the "keepers" and establish the film tight loop.

To meet all of today's demands in magnetic recording, the S6 is available for either 17.5mm or 16mm perforated film. The 16mm transport system operates at the conventional 36-feet per minute speed. In the 17.5mm recorder, advantage has been taken of the new trend toward use of 45 f.p.m. speed—one-half that of standard 35mm film. As both the frequency and motion exceed present standards, considerable savings in raw stock costs result through this halving of film travel speed.

One of the great problems with portable recording equipment has been the various voltages and currents encountered in the field. In the S6 this has been readily solved by the

RECORD AND playback electronic unit. Facilities are available for gain control of the record amplifier and playback amplifier, a five tape switch and a master switch to furnish volume indication, bias setting, and B+ voltage.

provision of facilities for quick change of both the gear box and the motor. It is possible to carry a 110-volt single-phase motor and a 220-volt 3-phase motor, along with a 50 cycle and a 60 cycle gear box, and to change from one complete system to the other without tools.

Basically, the specifications of the S6 are as follows: Frequency response—flat from 50 cycles to at least 12,000 cycles in both film speeds. The signal-to-noise is in excess of 55 db with less than 2% total harmonic distortion through the entire system. The transport system in the case weighs less than 24 pounds and the electronic section, less than 18 pounds. A 1000-foot film capacity is provided although obviously smaller amounts of film may be handled where desired. Either reels or open-flange type film holders may be used.

Perhaps the most outstanding feature of the Stancil-Hoffman S6 recording system is its flexibility and versatility. It is available as a one-, two-, or three-unit system for a wide variety of applications and uses. The three-unit system is virtually a major studio unit compressed into three light-weight components, easy to carry and to use, and provides for use of two microphones. The two unit package is for use with single microphone. The one unit is also a single microphone model and provides automatic volume control, making it ideal for such applications as newsreel, documentary and remote sound effects recording.

Any one of the three systems can be readily changed to operate as a one-, two-, or three-unit recording system, where the three components are available. Where the ideal sound recording channel uses a remote microphone preamplifier, permitting the mixer to operate at the scene of the action, many times this facility becomes a burden and unnecessary

(Continued on Page 550)

REAR VIEW of S6 transport unit showing the replaceable gear box and replaceable motor for either 50 or 60 cyc. 110-120 AC.



REAR VIEW of recording and playback amplifier sections. Removable panels provide for plug-in mike preamp or remote amplifier.

THE REPLACEABLE center section of the ARP6 amplifier system which contains the plug-in microphone preamplifier mentioned at left.



MODEL S6 transport unit with the open flanges and film guiding members affording fast loading and unloading of film.

POWER SUPPLY pack for the Model S6 is available in two models for 24-volt DC operation and for 110-volt single-phase power.

ROTARY CONVERTER which furnishes 230 volts 3-phase current from 24-volt batteries for powering heavy-duty 35mm equipment.

HARRY RUFFNER shoots a scene for his prize-winning film, "In The Heart of a Man," while his wife, Lee, acting as script girl, keeps a log on exposures. The two work together on all phases of their amateur film productions. Eric Osenda (right) is star of the picture. Camera is a Cine-Special mounted on a Kodak tripod.

Filming A Prize-winner

Cine Club film makers find that pre-production planning pays off handsomely in contest awards.

By CLIFFORD V. HARRINGTON

HARRY AND LEE RUFFNER of San Francisco, California, are a man-and-wife camera team that firmly believes that thorough pre-production planning is a necessity to the success of any amateur motion picture. Their most recent film, "In the Heart of a Man," is convincing proof of this theory. It was selected along with five other pictures to share equally the top honors in the annual contest of the Northern California Council of Amateur Movie Clubs.

The seventeen minute, 16mm color film with magnetic sound began as an idea nearly ten months before the Ruffners won their trophy.

"I always wanted to make a film about a hobo," Harry Ruffner said. "I wanted to depict a man, who for reasons known only to himself, has chosen to become a wanderer. In spite of the situations in which he finds himself, he still retains his dignity and self-respect."

After developing their basic theme, the Ruffners did not pick up their camera and rush into production. Instead, they began by putting their ideas on paper and working the kinks out of their brainchild. They spent two weeks developing the plot of their story and two months of spare time preparing a detailed shooting script.

The Ruffners' story traces the actions of a hobo who finds a wallet containing money. The wanderer visualizes the fine clothes he might purchase with the funds, but decides to return the wallet to its owner. The owner, a woman, rewards him with a five dollar bill. Deciding that his immediate need is a new pair of shoes, the bobo searches for a shoe store. On the way he passes a blind man. The hobo longingly inspects several pairs of shoes in a store window, but after careful thought he comes to the conclusion that he can do without new footwear a while longer. He gives the money to the blind man and continues on his way.

To play the main character of the hobo, they selected a friend, Eric Osenda of Sunnyvale, California. Osenda at first was skeptical of his ability to play the part. But after the demands that were to be made of him as an actor were explained, he changed his mind and entered enthusiastically into the project.

"When we write a script, we always keep in mind the persons who are going to play in the film," Ruffner said. "We try to incorporate as many of their characteristics and mannerisms as possible into the parts we are attempting to create. In this way we have a better chance of obtaining creditable performances, because, in a manner of speaking, they are playing themselves."

Osenda's wife, Evelyn, and his daughter, Loretta, were also given parts in the film. And before the shooting began the family's dog, Smokey, was included in the cast.

The Ruffners' pre-production planning did not end with writing a script and casting the parts. They spent three days searching the Santa Clara valley, nearly 50 miles below San Francisco, for locations. Before they began shooting, they made a three-minute test film of the lighting they planned to use in the interior shots.

The picture was begun in early spring and was planned so that the group could

(Continued on Page 556)



HARRY RUFFNER shoots main title for his prize-winning film on home-made titler that looks like a prize-winner also. Ruffner and wife are members of Westwood Camera Club, San Francisco.

Every scene has more life and sparkle when you use Ansco Hypan Film

This superior, all-around Ansco black-and-white movie film is made especially to put more snap and crispness into your personal motion pictures.

Ansco Hypan yields these outstanding results because it gives you fine-grain images with inherently brilliant contrast.

Hypan also offers the high speed (Exposure Indexes of 40 for daylight, 32 for tungsten) that permits you to take top-quality movies indoors or outside.

What's more, there's real economy in Hypan's low price. It lets you take more fine movies for your money.

Leading photo dealers everywhere have Ansco Hypan for 8 and 16mm cameras. Try Hypan Film soon and see how much more life-like your movie footage can be.

Ansco Binghamton, N. Y. A Division of General Aniline & Film Corp. *"From Research to Reality."*

Ask for Ansco Hypan Film

WHERE plane used for filming is equipped with intercom system, directions can be given pilot by the photographer durt g flight. Otherwise, series of hand signals, worked out beforehand, can be used to convey instructions to pilot

WHEN shooting from a helicopter with door cabin removed, wear safety belt provided for purpose. Vibration of craft makes it necessary to shoot cine cameras hand-held—never mounted or attached to helicopter structure

Shooting Movies From The Air

Advice for the cine amateur on how to shoot motion pictures from aircraft; also exposure determination procedure and filter data.

By DEAN RIGGINS

US Army Signal Corps, Ft Monmouth, New Jersey

YOU MAY SOMEDAY have opportunity to shoot motion pictures from the air, and if you do, the following information may prove useful. It is the essential information contained in the instructions this writer has given on occasions as Instructor of Newsreel and Combat Motion Picture Photography, United States Army Signal Corps Photographic School.

Since aerial scenes are generally of a nature not easily repeated, it is well to have sufficient foreknowledge of aerial filming techniques to guarantee successful results from the outset. It is assumed that the reader is already familiar with basic motion picture techniques, therefore only the additional requirements related to shooting movies in the air will be considered here.

There are three different types of aerial coverage: ground-to-air, air-to-air, and air-to-ground. Ground-to-air photography is similar to ground coverage and does not involve any particular change in techniques. The usual compensation for exposure (closing down 1 to 1½ stops) must be made, however, when shooting into the sky. Shots made of one plane from another near-by plane, when both are in flight, is called air-to-air coverage. The filming of a ground subject from a plane in flight is

termed air-to-ground coverage. Most aerial assignments will call for the latter type of coverage.

When filming from the air the three greatest problems are: locating your "target" or subject, reducing picture shakiness to a minimum, and eliminating the effects of aerial haze. Each of these problems will be considered in turn.

The "target," or subject (if not familiar to your pilot) should be checked in advance on his flight map. In a joint briefing the entire mission and events (insofar as they are known or predictable) should be discussed, and a complete understanding of the "target" location, the direction of approach, the direction of circling the "target," and the desired altitudes for filming should be reached. These decisions are largely up to the cameraman. At all times, in aerial photography, close coordination and co-operation between the pilot and the photographer is essential.

The pilot will be concerned with the safety of his passenger or passengers, and compliance with flying regulations. He will brief you on the use of the safety belt and how to get into your parachute harness, if one is to be worn. For communications between photographer and pilot, most planes are equipped with an inter-com system. The pilot will probably brief you on the proper use of the inter-com "mike" and headphones. If the plane has no inter-com, appropriate hand signals should be decided upon prior to the flight.

When filming from a light plane or a helicopter the cameraman's shooting position is not left to choice. If called upon to shoot from a larger plane, however, it is advisable to take a position in the nose or well toward the tail structure of the plane. In either position the angle of vision is fully adequate, so it is seldom necessary to shoot from right angles to the craft.

Movies taken at right angles from a plane tend to be choppy. The "target" is passed more rapidly, consequently your shooting time is shorter. Unless your subject is quite a distance away, you will pass the "target" too quickly to attain proper scene length.

When possible, aim your camera a little forward or to the rear. The subject will stay in your field of view for a longer period of time, and any lurching of the plane will be less apparent, when screened, due to the greater camera to subject distance.

In certain instances you may be compelled to shoot at right angles to your line of flight, as when filming from an "open cockpit" type of plane, where the shooting field is broken by wing and tail structures, or when shooting air-to-air coverage of an aircraft flying parallel to you.

Steady support of your camera is another important factor in obtaining a smooth, steady, screen image. In a light plane there is usually a considerable amount of vibration. Therefore it is not advisable to attempt rigid support of any but the heavier production-type cameras. When filming with a 16mm or 8mm camera, hand-hold the camera while shooting and *avoid any attempt to steady or support it on the window ledge* or any other part of the plane. Keep elbows in close to your body. Avoid any contact with the plane except for the seat, and the placement of your feet on the floor. Although you should not lean against the window, it is important to lean as close to the window as possible and keep your camera substantially higher than the lower edge of the window opening in order to avoid image cut-off if the plane should hit some rough air.

In filming with a camera that is too large to hold by hand, mount the camera on a tripod or some improvised support. In some cases a specially devised shock-absorbent rubber section may be attached to the base of the camera and then mounted on the supporting tripod. In the larger type planes a support is generally used regardless of the size of the camera. Some cameramen use the so-called "Hi-hat," which is a very short tripod with a solid fixed-leg structure and holes at the base of the legs for bolting down. This is a decided advantage because any tripod used in aerial work should be bolted or tied-down securely.

All these factors—position in the plane, filming angle, and camera support—play an important part in obtaining a steady image, but there are still others yet to be considered. The first of these has to do with the degree of shutter opening (D.S.O.) in relation to percentage of frame overlap of the terrain being photographed. (This will not concern the average amateur unless he uses a variable shutter camera, such as the Cine-Special.) Contrary to popular belief, a narrow shutter opening will not neutralize the effect of vibration. While each picture may be slightly sharper with a small opening, they will be apt to flicker when projected. It is better to sacrifice extreme sharpness than to have too great an interval of terrain movement between frames. The resultant flicker from a narrow shutter opening becomes even more pronounced as the plane speed increases. It is good practice to use the largest possible shutter opening which will stop motion.

With the smaller cameras having fixed shutters no adjustment, of course, is possible. But on variable shutter models, the shutter should not be closed down beyond the 100° mark.

Increasing the number of frames-per-second will also greatly aid in compensating for the speed of the plane, and

(Continued on Page 552)

FILTERS are an inevitable necessity when shooting from the air. They make it possible for the lens to penetrate fog, smog and haze to produce an image of the scene much more distinct than it appears to the eye.

MOVIOLA

FILM EDITING EQUIPMENT

16MM - 35MM

- PICTURE SOUND Photo and Magnetic
- SYNCHRO-NIZERS
- REWINDERS

One of the new series 20 Movielas for picture and sound

Write for Catalogue



MOVIOLA MANUFACTURING CO.
1451 Gordon St ■ Hollywood 28 Calif

RUBY CAMERA EXCHANGE
Rents . . . Sells . . . Exchanges

●

Everything You Need for the

Production & Projection

of Motion Pictures Provided by a Veteran Organization of Specialists

35 mm. . . . . 16 mm
Television

IN BUSINESS SINCE 1910

729 Seventh Ave., New York 19, N Y
Tel: Circle 5-5640
Cable address: RUBYCAM

FILMING "THE AFRICAN LION"

(Continued from Page 535)

the cameras were focused on the subject and filming began on one of the most interesting sequences for "The African Lion."

Traveling over the great prairie distances naturally consumed considerable motor fuel. To avoid running out of gas at a dangerous or inopportune time, Milotte cached 50-gallon drums of gasoline at various points within the area selected for photography. As the drums were emptied, they were returned for refilling on the next trip to Nairobi.

In addition to the four-wheel drive truck previously described, the Milottes also brought along a British version of the Jeep, called a land rover. This served the dual purpose of insuring transportation in the event the truck broke down, and a light, fast mode of transportation for certain filming situations.

No natives or other helpers accompanied the Milottes into the African wilds. They traveled alone, except for an occasional visit from a Park ranger—one driving the Jeep and the other the truck. The most fearful moment of their whole African adventure came one evening when a big herd of elephants, led by enormous tusked bulls, crowded in around a water hole. Elma was caught by surprise and had to scamper up a tree and take refuge on a half-constructer camera platform. There she remained, crouched on a single plank, too terrified to move for hours until night fell. Al and a visiting Park ranger were trapped inside the truck some distance away and could not come to Elma's rescue. Much later while the beasts were busy with their bathing, they slipped through and got her down from her perch. Back in the truck, the trio remained hidden and quiet all that night and until noon the next day when the elephants finally dispersed. They could have pushed the truck over and wrecked it at the slightest alarm.

Another close call occurred in a remote region when Milotte and a Park patrol officer rescued a rhino from certain slow death in a mud trap. They hauled him out with heavy ropes attached to the truck. In repayment, the rhino upon being freed, charged Al. He fled to the truck just a few yards ahead of the deadly pitching horns. All the while this was going on, Elma, who was shooting the rescue, stuck to her guns and photographed her husband's narrow escape, stopping the camera only when the charging rhino hit the truck's front bumper with a shock like an earthquake.

To select a family group or an individual for close study from the welter of creature life was a bewildering experience for the Milottes when first they set out from Nairobi in their specially built four-wheel-drive truck. Yet, as they got their bearings, they learned that their quarry had to be stalked and found anew every day, despite its incredible profusion. The hunt for food and water, sudden migrations, weather conditions and unaccountable mass moods made the presence of grazers and predators alike unpredictable. As their subjects moved, the Milottes had to move. Gradually, the pattern of mid-African animal behavior became understandable — and predictable to some extent.

In addition to carefully-chosen equipment and a knowledge of wildlife lore and the African terrain, the Milottes success as wildlife photographers is attributable to still another quality—that of infinite patience. For this kind of photography involves more than anything else the technique, if we may call

EVERYTHING PHOTOGRAPHIC
AND CINEMATIC
FOR PROFESSIONAL AND AMATEUR

The World's Largest Variety of Cameras and Projectors Studio and Laboratory Equipment with Latest Improvements as used in the Hollywood Studios New and Used . . . BARGAINS Established 25 years



HOLLYWOOD CAMERA EXCHANGE
1600 Cahuenga Boulevard
HO 9-3651 ● Hollywood, Calif. ● Cable Hocamex

MAIN TITLES • FADES • DISSOLVES • WIPES • SUPERIMPOSURES

OPTICAL EFFECTS
35mm or 16mm

MATTES • INSERTS

●

Write or Call Ray Mercer

BLACK and WHITE
or COLOR

FOR SPECIAL PHOTOGRAPHIC EFFECTS INFORMATION AND OPTICAL CHART

RAY MERCER & CO.

4241 NORMAL AVE., HOLLYWOOD, CALIF. • NOrmandy 3-9331

The One-Stop Source Of Supply

S.O.S. Has YOUR BEST DEAL

ON

The ALL NEW AURICON PRO-600

for 16mm Optical Sound-On-Film

"Auricon Pro-600" with Lens Blimping Head, Auto Parallax Finder with Magazine, Tripod

Professional Picture Camera with Built-in Features

'Auricon Pro-600' with Single Lens "C" Mount, Tele Finder Objective, View Finder, Magazine



'Auricon Pro-600' with Critical Ground-Glass Focusing, 3-Lens Turret

★ Self-blimped for completely quiet studio operation. The whisper-quiet film flow of The Auricon Pro-600 is silent proof of precision design. Your sound recording microphone never picks up Pro-600 Camera noise!

★ 400 ft. film Magazines with Auricon-Electramatic Take up... for 16 minutes of continuous "Talking Picture" filming.

★ Synchronous Motor Drive for "Single-System" or Double-System Recording...

★ Available at added cost is — Single System equipment for Optical Sound-Track-On Film, "C"-mount Lenses, Film Magazines, View Finders, 3 Lens Turret, Critical Ground-Glass Focusing Lens, Sun Shades, Tele Finders, etc.

★ Sold with 30 day money back guarantee, you must be satisfied!

PRICES START AT $1165

Write for free illustrated "ALL NEW Auricon Pro-600" literature and prices

SPECIAL OFFER to AURICON-PRO OWNERS

S.O.S. will accept your old camera as a trade-in for the "All New Auricon Pro-600". Time Payments, Too!

The Answer to Economy in Animation

TEL-Anima
PRECISION PRODUCTS
REG. U.S. PAT. OFF.

TEL-Animaprint

The first sensibly priced Hot Press Title Machine for high quality, fast lettering. Prints dry from colored foil for instant use. Acme pegs give perfect registration on paper or acetate cells.

For Perfect Titles... Prints All Colors... 25" high 14" wide 18½" deep

PRICED FROM **$395**



TEL-ANIMA tools for Top Techniques... Greatest dollar for dollar value in the industry!

TEL-Animastand

A professional Animation Stand with accuracy guaranteed by Acme Peg Bar registration. Includes all basic movements—does everything the animator needs. Engineered to meet the most limited budget.

FOR MOTION PICTURE PRODUCERS, ANIMATORS, SPECIAL EFFECTS LABORATORIES, TV STATIONS, ADVERTISING AGENCIES, ETC.

12" to 4" Field Widths... Moves E-W, N-S 6'4" high 42" wide 43½" deep

PRICED FROM **$1995**



Write for brochure

Manufactured and distributed exclusively by S O S

"The Department Store of the Motion Picture Industry"

S.O.S. CINEMA SUPPLY CORP.

602 WEST 52nd ST., NEW YORK 19, N.Y.
Phone: PLaza 7-0440 Cable: SOSOUND

S.O.S. EST 1926

HOLLYWOOD, CALIF. OFFICE—Dept. F, 6331 Hollywood Blvd., HO 7-9202—*For Other Important S.O.S. Offerings See Pg 516*

PRECISION RACK-OVER
For all Bell & Howell 70 Cameras
Also adaptable to Bolex H-8 and H-16 Cameras—3.00 additional
PRICE
$28.50



PHYSICAL DESCRIPTION
Size 4⅛"x4¼"x2¼" high
Weight: 3½ lbs approx
Cast Iron
Wrinkle Enamel finish
Machined to .001 tolerance
Tool Steel Guide and Lock Pins
Viser Spring Locating Plunger

FEATURES
- Film **exactly** what you **see**
- A must for perfectly centered titles
- Perfect for **animation** Assures you all moving objects are within the lens field
- Film **ultra close-ups** not possible with camera parallax adjustment
- Mounts on any tripod using ⅜ 20 mounting screw
- **Cam locks** in position to avoid accidental loss of field
- Camera can be **hand cranked** regardless of position on **RACK-OVER**
- A substantial **camera base** used to film from a table top
- May be used with **all** camera accessories in place such as: motor 400 ft magazine etc
- Can be racked over and locked **instantly**

NOTE—Accessories soon available to mount directly on the **RACK-OVER** Precision Matt Box—Titler Attachment

CINE PRODUCTS COMPANY
P O Box 135 Westlake, Ohio

Convert Your Auricon Pro or Cine-Voice to Accept 400-ft Magazines

Shoot Complete 50' Television Programs!

A completely satisfactory custom conversion to use 100' spools, 200' spools or 400' magazines for direct recording of 16mm sound movies. Your camera is entirely rebuilt, refinished and converted or we can supply complete new units on order.

Direct drive (no lag or speeding up at film). Conversion includes built in Veedor foot age counter and monitor phone jack. We can also supply fully synchroneus motors. Thoroughly tested and approved. Prompt delivery.

Write for Literature and Prices

We are also distributors for HILLS FILMATIC 16mm Processor

HAROLD'S Photography & TV
308 South Phillips, Sioux Falls, S D

it that, of *watch and wait*—where the price of success is eternal vigilance.

Al Milotte says that perhaps their greatest enemy was not the ever-present danger of attack from animals or of being suddenly marooned in danger areas but the nervous strain induced by the steady vigilance necessary to capturing the rare shots that have made "The African Lion" such a success. There were days when scarcely a usable shot was made with the cameras. Yet it was necessary for both Al and Elma to sit quietly, for hours, sometimes, eyes fixed on a clump of trees or brush where a suspected subject might suddenly emerge. This is the sort of life these two intrepid nature-loving, camera addicts endured for two years and eight months in order to shoot 100,000 feet of 16mm Kodachrome, out of which Disney technicians selected and put together a mere 6,000 that is being released next month as "The African Lion."

MAKE-UP MAGIC FOR TODAY'S COLOR FILMS

(Continued from Page 528)

with each new advance in negative manufacturing progress, make-up techniques and colors are devised to take fullest advantage of the film while, at the same time, compensating where possible for the unfortunate properties remaining in each individual type of film. Check your film advances and changes constantly, to keep step with the required changes in make up requirements. As Max Factor, Jr. says: "Only continued care and observation of make up can serve to produce a successful effect under rapidly-changing types of new film emulsions."

SUGGESTED MAKE-UP CHART FOR 16MM KODACHROME

	WOMEN			MEN		
	FAIR	MEDIUM	DARK	FAIR & MED.	DARK	TAN
Pan Cake Make-Up or Pan Stik	23M	Tan 1	Tan Rose	Tan 2	K 1	K 2
Make-Up Powder	Olive Natural	Deep Olive Natural	Natural Tan Olive	Golden Tan Sun Tan	K 1 Sun Tan	K 2 Sun Tan
Creme Rouge	Rieedeen	Rieedeen	Rieedeen			
Dry Rouge	Clear Red 1	Clear Red 1	Clear Red 1	Dark Tash	Dark Tash	Dark Tash
Eye Shadow		Brown or Grey			Brown	
Moist Rouge (Lips)				T-3		
Eyebrow Pencil	It. Brown	Brown	Black		Brown or Black	
Eyelash Make Up	Brown	Brownish Black	Black		Brown or Brownish Black	
Lipstick	Clearly Red	Clearly Red	Clearly Red			

For Tanned effect on women, use Tan No 2 Pan Cake, or Golden Tan Pan Stik
For Pink shade of lipstick, use Party Pink; for pink orange shade, use Coral Sprayr for rose shade, use Red Red Rose
For outdoor shooting use cheek rouge over a larger area on cheeks to prevent loss of color, especially if reflectors are used

PRE-PRINTING PREPARATION OF 16MM FILMS

(Continued from Page 531)

Dissolves: It is suggested that 48 frames be used as a standard overlap in preparing A & B rolls for dissolves. (Fig 1). This does not necessarily mean that the length of the printing effect will be 48 frames, but it will permit laboratories to make dissolves of varying lengths up to two seconds duration.

Some laboratories request that a number of extra frames be left on the head and tail of each scene in matching. For this reason the laboratory used should be quizzed and their recommendation followed.

Series of Effects: When dissolves or fades follow each other at very short intervals, caution should be exercised; for the film editor should remember that on a single roll, no new effect can be started before the last effect is completed. It is impossible, for example to start a fadeout after a fadein until the fadein cycle is completed in the printer. With a standard of 48 frames overlap, it is recommended that the minimum length of a scene that incorporates an effect at each end be no shorter than 108 frames in the original A & B rolls—i.e., 48 frames for the fadein and 48 frames for the fadeout, plus an additional 12 frames as a safety factor. This scene, in the cut work print, would then be no shorter than 60 frames.

Dissolves Following Cut-Across: If a dissolve or fade follows black leader after a cut-across scene in the original A & B rolls, it is recommended that the black leader be no shorter than 54 frames. This allows 48 frames for the mechanical fader to fade out in order to

NOW... MATCH EITHER WHITE OR YELLOW LIGHT FILMS WITH NATIONAL STUDIO ARC-CARBONS

TRADE-MARK

The advantages of carbon arc studio lighting have long been recognized. Until recently, however, it was necessary to filter carbon arc sources very heavily when shooting on a yellow-light hasis.

Now, with the new "National" yellow-light studio carbons, you can freely mix arc lamps and inkies on the same set with minor filtering and virtually no loss of useful light. This new carbon nearly douhles the effective light from arc sources without additional power input — or, where arc-lighting is essential for hroad coverage, penetration or modeling, it reduces hy almost half the number of arc lamps needed for 3300°k film.

Here, again, National Carbon's research facilities, prompted hy the company's long association with progress in film-making, have paved the way to suhstantial production economies without compromising the industry's high standards of excellence.

The term "National" is a registered trade-mark of Union Carbide and Carbon Corporation

NATIONAL CARBON COMPANY

A Division of Union Carbide and Carbon Corporation

30 East 42nd Street, New York 17, N.Y.

SALES OFFICES:
Atlanta, Chicago, Dallas, Kansas City Los Angeles, New York, Pittsburgh, San Francisco

IN CANADA:
Union Carbide Canada Limited, Toronto

CINEKAD
JUNIOR TRIPOD DOLLY

This collapsible three wheel tripod dolly is especially designed to meet the demand for convenient mobility of cameras on location or in the studio
Dolly can be used with any professional or semi pro tripod
The tripod is fastened firmly to the dolly by a clamp at each leg tip
The special individual caster locking system makes it possible to lock either two or three wheels in a parallel position, enabling the dolly to track in a straight line for rolling dolly shots
Dolly folds quickly into a single compact, easy to carry unit, 23 inches in length, weighing 14 lbs

Write for Prices and Literature

CINEKAD
ENGINEERING COMPANY
500 WEST 52ND ST., NEW YORK 19, N Y
Plaza 7-3511
DESIGNERS AND MANUFACTURERS OF MOTION PICTURES AND TV EQUIPMENT

LAB-TV
Professional
16MM BLACK & WHITE
REVERSAL
PROCESSING
•
Processing on hourly schedule for leading TV Stations and Producers
•
FASTAX SPECIALISTS
•
Write for Circular
247 W. 46th St.
New York 36, N. Y.

be ready for the fadein on the beginning of the following effect scene. The 54 frame length allows 6 frames as a safety factor. The same recommendation applies when the effect precedes the cut-across.

Marking Dissolves: It is suggested that the middle of each dissolve be marked by making a small "x" in each of two adjacent frames in the center of each fade, on both the A & B rolls. These marks should be made on the emulsion side of the film—outside the picture area. They will appear in the center of the effect on the perforated edge of the film (not the track edge). The two "x" marks in the A roll will then be exactly opposite the two marks in the B roll, when both rolls are placed correctly in a synchronizer. Thus, the dissolve overlap can be easily checked and correct synchronization of the rolls verified. The emulsion can be scraped by a scriber to form the "x" marks or they can be made with a pen and white, waterproof, quick-drying ink.

Splices: The original should be spliced with the utmost care. It is recommended that before splicing any original, several test splices be made in order to check splicer for correct alignment and for depth and width of the scraped area of the film. Use only enough cement to insure a good splice. Avoid winding a wet splice onto the roll where it may mark the next layer of film.

Instructions to Laboratory. Instructions should accompany each film when it is sent to the laboratory by the producer. These instructions should specify in detail all special effects desired. When footage figures are given to indicate the point where effects are desired, measure the footage from the printer start mark in the head leader. *Do not* use paper clips, grease pencil, Scotch Tape, string, etc., to indicate where effects are desired in the film. Kum Kleen labels can be used, applied to the film itself with safety. These should be placed on the black leader instead of in the scene and on the emulsion side of the film.

The Association's recommendations governing the method of marking work prints to indicate effects includes six specifications: (See Fig. 2).

Fadein: A fadein should be indicated by two straight lines forming a long "V". The two lines should run diagonally for the length of the effect from the edges of the film and converge at the center of the frame at the point of scene change.

Fadeout: The procedure is the reverse of that for the fadein—the lines extending for the length of the effect and meeting at the center of the frame at the point of scene change to indicate where the screen will be totally dark.

Dissolve: A dissolve is in actual practice a fadein of one scene superimposed over a fadeout of another. To indicate a dissolve on a workprint, the markings should be the same as those used for a fadein and a fadeout, but they should in this case overlap each other, as shown in the diagrams. The mid-point of both markings should occur at the splice in the work print and the markings should extend an equal distance into both scenes.

Double Exposures: Double exposures, superimposed titles, etc., should be indicated by cutting into the background scene of the work print a few inches of edge-numbered work print of the new superimposed scene, to indicate where the double-exposure begins. Several inches of the superimposed scene should then be cut in to indicate the end of the double exposure. These two pieces should be connected together by a wavy line.

To insure proper matching, it is essential that one of these small pieces of work print be edged-numbered or identified in some way.

Extended scenes. Scenes to be extended in matching that are indicated in the work print by leader should be marked with a long arrow, the shaft of which is drawn through the leader and the head of which comes up to the last frame of the leader to indicate the length of the extension.

Unintentional Splices. Splices occurring in the work print that are to be disregarded in matching should be indicated by two short parallel straight lines drawn through the splice and at right angles to it. This indicates that the scene is not to be cut at that point.

The Association emphasizes that all marks on work prints be made with a yellow grease pencil. Yellow is recommended because it shows up well on both color and black-and-white films. If any cues are made on the work print for recording or mixing, it is suggested that a red grease pencil be used for this purpose.

The Association has also prepared recommendations for "Preparation of 16mm Printing Leaders," which will be the subject of another article in American Cinematographer next month.

MOVING?

When changing your address, please notify us at least four weeks in advance. BE SURE to give your Former address as well as your New address. Our Circulation Department needs both addresses in order to properly identify your address stencil.

Your cooperation will insure that American Cinematographer will continue coming to you regularly without delay or omission of issues. Thank You.

—American Cinematographer

PHOTOGRAPHY AT 40,000 FEET

(Continued from Page 533)

SAC. Thanks to his cooperation, our company was assured the use of as many planes as we wanted as long as our demands did not interfere with SAC's training program.

One of the last things we did before starting photography of the air sequences was to prepare charts and instruction booklets outlining flight procedure for each take. These were distributed among the group leaders and pilots and to the General at the Air Force base. In this way, the men handling the planes in the air had their instructions in writing as to what action was required, and this went a long way toward minimizing errors and the need for retakes. Augmenting the charts and booklets were the briefing periods which preceded each flight, when all flight personnel and our production personnel assembled in the briefing room. Here, with the aid of blackboard diagrams, the whole flight procedure was explained and our filming requirements outlined.

The in-air refueling operation, which appears in the picture, marks the first time that this operation has ever been photographed for inclusion in a feature film. Tom Tutwiler shot this sequence from Paul Mantz's camera plane, with Mantz at the controls.

At one time while Tutwiler was in the air shooting a sequence of shots, I took to the air in a B-47, from which the canopy had been removed, and made shots showing the effect of air turbulence on the wing surfaces of the plane This same plane was used again later, with a camera mounted underneath, to record closeups of the plane's giant landing wheels in action.

There have been many cinematographers in Hollywood who have become famous for their ability in aerial photography Tom Tutwiler, who was an Army Air Force cameraman with rank of Captain during World War II, is one of these Tom therefore was right at home on this assignment, and especially so in Paul Mantz's B-25; he had done most of his Air Force photography from this type plane during the war.

Filming the story of the Strategic Air Command was the idea of actor Jimmy Stewart, who stars in the production As a human document "Strategic Air Command" is revealing As a first opportunity to see this amazing organization in operation it is most exciting And the broad sweep of VistaVision photography makes this panorama of skyborne grandeur something to be remembered.

Kinevox®

16mm Synchronous Magnetic Film Recorder



$695.00

A precision-mode unit designed and engineered for 16mm magnetic film. Filtered drive between synchronous motor and precision sprocket. One compact unit houses both transport mechanism and amplifiers

Write for descriptive catalog on complete synchronous recording equipment and accessories

KINEVOX INC.

KINEVOX BUILDING
116 S HOLLYWOOD WAY
BURBANK, CALIFORNIA

Telephone: Victorie 9-3291

CABLE: KINEVOX, BURBANK

NO MORE NEGATIVE NOTCHING



DUNNING MAGIC DOT PRINTER CUEING UNIT

COMPRISES—(1) Supply of high-conductive Anson made pressure adhesive tape (2) Special punch for cutting, affixing and positioning Magic Dots to film edge (3) Roller contacter to instantly fit Models D or J BBH printers (4) Electrical control box for activating light change and fader impulses.

Consolidated Film Industries' installation reports "Over 90,000 changes without a miss"

Complete 4 port unit, **$360.00**

ANSON RESEARCH CO.
4337 Clybourne, North Hollywood, Calif

Advantage Never Before Offered!

SWIVEL BALL JOINT ATTACHMENT

for

PRO JUNIOR and F & B TRIPODS

Swivel Ball Joint Attachment can be mounted between head and tripod body in a few seconds and without any technical knowledge. Swivel Ball has enough lightening strength to hold the largest and heaviest movie cameras, permits leveling camera quickly when tripod is set up on uneven ground. Ball Attachment is made of lightweight aluminum, weighs approx 3½ lbs.

Ten Day Money-Back Guarantee
Write for Catalog and Prices

CINEKAD
ENGINEERING COMPANY
500 West 52nd St., New York 19, N Y
PLaza 7-3511

DESIGNERS AND MANUFACTURERS OF MOTION PICTURE—TV EQUIPMENT

EXPOSURE DETERMINATION

(Continued from Page 524)

—Unnecessary to change aperture in panning from light to shade.
—Ability to get sharper definition—to stop the action—in shooting high speed action at normal f.p.s., by reducing the shutter opening.
—Eliminates need for using ND filters when shooting fast black-and white film in bright sunlight.
—Unnecessary to cap lens when rewinding for lap-dissolves. Shutter is closed instead.

The previously-mentioned cameras afford a range of four shutter openings (or speeds): Open, ¾-open, ½-open, and ¼-open. With the camera operating at 16 frames per second, it affords a range of shutter speeds from 1/35th second to 1/40th second.

The following table enlarges on this and shows the great range of shutter speeds available to the photographer whose camera provides for *camera* speeds ranging from 8 to 64 frames per second.

		Shutter Openings			
		Open	3/4	1/2	1/4
Camera Speeds	8 fps	1/18	1/26	1/35	1/70
	16 fps	1/35	1/53	1/70	1/140
	24 fps	1/53	1/70	1/105	1/210
	32 fps	1/70	1/105	1/140	1/280
	64 fps	1/140	1/210	1/280	1/560

NOTE. Because the exposure difference is almost negligible, even numbers can be substituted for certain odd numbers in the above chart. For example:

16 fps: 1/30 for 1/35
24 fps: 1/50 for 1/53
32 fps: 1/60 for 1/70
64 fps: 1/120 for 1/140

From the above table it may be seen that the Cine photographer has available to him the same means of "stopping" fast action as does the still photographer with a Graflex or Speed Graphic camera. When shooting fast-action subject matter such as water skiers, or when shooting from a fast moving car, such action can be shot at 24 f.p.s. sound speed and 1/210 second shutter speed to gain blurless, high-definition results in cine photography.

When panning from deep shade to bright sunlight with a fixed-shutter camera, exposure consistency is normally maintained (when this is desired) by changing the aperture as the camera moves from shade to light. This not only involves changing the depth of field but usually requires a camera assistant to manipulate the lens diaphragm as shooting proceeds. Where the camera has a variable shutter, it can be operated as the camera is running by the photographer.

Now that we understand these advantages, our next problem is knowing how to readily determine the correct exposure for the various shutter speeds, in view of the fact that meters which do indicate cine camera exposures are usually calibrated for the standard silent speed of 16 frames per second. Some meters, such as the Norwood "Director," have the "frames per second" camera speeds inscribed on the computer dial as an aid to calculating exposures for cine cameras. For illustrative purposes, the author shows the comparative shutter openings of variable shutter cameras, such as the Cine-Special (See Fig. 1). The arrow points to the "Cine Frames" figures, otherwise known as the frames-per-second figures. Opposite the author's lettering 'Shutter Opening" appear the figures for same. "O"—fully open—appears above the 16 f.p.s. figure, ¾ over the 24 f.p.s. figure; ½ over the 32 f.p.s. figure; and ¼ over the 64 f.p.s. figure. The figures in either row (of the author's illustration) are synonymous and can be memorized for future use. Also, it is suggested that for reference the illustration of the marked meter dial (Fig. 1) be clipped from the magazine and carried conveniently with the meter.

To explain further the use of these comparative figures for those using cameras with variable shutters, let us take a hypothetical situation: Using color film in a Cine-Special operating at 16 f.p.s., the subject must move from deep shade to bright sunlight, with no break in the action. Our first step is to take a normal reading in the shade—the meter registers f/4. Next we take a reading in the sun—f/8. (See Fig. 2). Now our problem here is to maintain uniform exposure, going from shade to light, without altering the camera speed. This will be accomplished by gradually

PRECISION SOUND READERS

Look for this trademark



It is your guarantee of the finest in sound editing instruments.



OPTICAL
Model 800 16mm and 35mm
NET PRICE $185 00

MAGNETIC
Model 700 16mm, 17 5mm, 35mm and ¼ inch
NET PRICE $198 00

OPTICAL-MAGNETIC
Model 800 16mm, 35mm & ¼ inch
NET PRICE $259 50

FEATURES: Simple threading . . . polished stabilizer drum with needle bearings, with a surface which cannot damage film . . film rollers machined to conform with SMPTE standards, and equipped with oilless bearings . . . precision ground shafts . dimension 6x6x7 ½ inches.

AMPLIFIER: 117 volt — 60 cycle — AC power output — 4 watts . . . heavy duty Alnico V speaker . . . safety fused . . . prefocused socket . . pilot light . 6 ft. heavy duty cord

All Prices F. O. B. Factory, Brooklyn, New York

Write for Literature

PRECISION LABORATORIES
1130 UTICA AVENUE • BROOKLYN 3, NEW YORK

closing the shutter as the camera pans from shade to light. But how much shall we close it? A glance at the meter dial shows that f/4 (the shade reading) appears opposite the ¼-open shutter mark (2, in Fig. 2). This indicates that the variable shutter can be moved from open to ¼-open in full sun to maintain the same exposure during the panning of the camera.

To clarify this, the lens is set at f/4 at the beginning of the pan (in shade) and the shutter in open position. As the camera is panned, the shutter control lever is gradually moved until shutter is closed down to the ¼-open position when the camera's field of view reaches full sun. Thus the shutter speed of the camera during the panning action ranges from 1/35 second (in open position) to 1/140 second at conclusion of the shot when it is stopped down to ¼-open position. The lens aperture, meanwhile, remains constant at f/4, the amount of light reaching the lens is controlled—and kept uniform—by gradually closing the shutter.

Another example of the extended usefulness of the modern exposure meter is its ability to determine the lens opening to use when shooting high speed action in slow motion. With the Cine Special, this would be at 64 f.p.s. Let us say that we have decided to use the smallest shutter opening — ¼-open —

Charles Ross INC.

EVERYTHING FOR EASTERN PRODUCTION

- LIGHTING -
GRIP EQUIPMENT
PROPS - GENERATORS
DOLLIES - MICROPHONE BOOMS

(Catalogs Upon Request)

333 WEST 52nd ST. N.Y. 19, N.Y. CI 6-5470

Now! A 400ft. Magazine For Your BOLEX H-16

Complete with Synchronous Motor and Bose

•

Includes Installation and Case

Permits continuous 400 ft. run of 16mm film—the 200 ft. daylight loading spool may be used in the 400 ft. magazine. The 100 ft. spool can be used in the camera without removing external magazine. Fully guaranteed. Can YOU shoot a continuous wrestling match, prizefight or football game? If not write for complete information or see your Bolex dealer

Ask about our Rack-Over, Sportsfinder and Camera Base.

TOLEDO CINE ENGINEERING
1309 Millburn Ave. Toledo 6, Ohio



Automatic dissolve attachments for Cine Special and Bolex H-16 and 8 (Equipped with Pellegrini Shutter)
JOSEPH YOLO 1037 N. La Brea
Phone GL. 7103 Hollywood, California

Video Film Laboratories
131 West 23rd Street
New York 11, N.Y.

Complete 16mm laboratory service for Producers using the Reversal Process

Also 16mm Negative and Positive developing

WRITE FOR PRICE LIST

Established 1949

Scheibe FILTERS
In World-Wide Use

Produce moonlight and night effects in daytime • fog scenes • diffused focus and many other effects

Information mailed on request

SCHEIBE FILTERS COMPANY
ORIGINATORS OF EFFECT FILTERS
P. O. Box 46834, Hollywood 46, Calif.

which would give an exposure of 1/560 second (See table), and we wish to know what the aperture setting should be. An exposure meter reading of the existing light shows the value to be f/8 at 16 f.p.s. (1 in Fig. 2). Checking this same dial setting it is noted that the exposure at 64 f.p.s. is 1/4 (2 in Fig. 2). We then set the *16* of the Cine Frames dial over the f/4 mark (3 in Fig. 2), and a glance at the exposure figure for the ¼-open shutter positions shows it to be f/2 (4 in Fig. 2)—the lens setting for the 1/560 second shutter speed.

Taking a reverse situation—shooting at 8 f.p.s. in order to speed up action on the screen, *but at a higher shutter speed* than afforded by the normal fully open shutter. An exposure meter reading of the light shows it to be the same as in the example above, i.e., f/8 at 16 f.p.s. Referring to the figure 8 (for f.p.s.) on the Cine Frames dial of the meter, we note the aperture setting for this camera speed is f/11. We next set the figure 16 of the Cine Frames dial over the f/11 mark and refer to the exposure indicator under the ¼-open mark which is f/5.6, giving a shutter speed at 8 f.p.s. of 1/70 second.

The ¼-open shutter position was selected for illustration in the above instances only as an example. The same procedures would apply for the ½-open or ¾-open positions. Selection of shutter opening, of course, will sometimes depend on how fast a shutter speed is required to "stop" certain fast action and prevent blur.

Because the variable shutters of the cameras considered here all give the basic exposure of 1/35 second at 16 f.p.s., the aperture figures for other f.p.s. speeds may appear in amounts not corresponding to the even figures found on most exposure meter dials (See table on page 548). In most cases, the difference is so slight as to be disregarded, but critical workers may wish to change to another aperture by electing to shoot at a different shutter opening.

For example—shooting high-speed panchromatic film out of doors, the meter reads f/28 at 24 f.p.s. But the smallest aperture afforded by the camera lens is f/22. A glance at the modified meter dial shows that a stop of f/18 can be used instead by shooting with the shutter in the ¼ open position. END

NEW S6 MAGNETIC RECORDER

(Continued from Page 537)

where only a single microphone is used. In the two-unit system, all functions are available such as recording gain control, playback gain control with a selective switch for "Live" and "Tape," dialogue equalizer, and adjustments for optimum frequency response.

The single case unit employs Stancil-Hoffman's recently developed subminiature compression recording and playback amplifiers. Incidentally, this electronic section, complete with its dry batteries, weighs a mere 3¾ pounds. The compression feature offers a wide latitude of sound pick up so that it is possible to record the speech of a moving person ranging from microphone position up to a distance of 10 to 15 feet away, with the recording level remaining constant.

All of the units are uniform in size. Panel is 14½" x 10¾". Depth of each unit is 6". To keep weight at the absolute minimum, a durable, flexible "Royalite" plastic case encloses each unit. Case is held in place by two thumbscrews, which also secure the handle and four rubber feet. The case may be removed in a matter of seconds to permit access to the mechanism components. Choice of the "Royalite" case was predicated on the desire to provide equipment with lowest possible weight for low-cost aerial or express shipment.

While the model S6 is said to represent one of the major advancements in portable magnetic sound recorder design, the most interesting feature perhaps is the system's adaptibility for battery operation. With sound systems through the years a wide variety of battery voltages have been used. Generally no consideration has been given to the power facilities necessary for the camera, although the chief purpose of a field recording system is to provide lip-sync sound with a minimum of equipment.

In designing the S6, a study of the efficiencies of batteries indicated that a 24-volt battery was the most ideal, considering weight and size, and it was made the basic power source for operation of both camera and sound equipment.

All amplifier filaments of the S6 work in 24-volt strings which can be directly tied across the battery. The amplifiers may be operated from "B" batteries, but a tremendous amount of weight is saved through the use of a small dynamotor which is an integral part of the system, and which operates from the 24-volt battery to furnish 250-volt output. The dynamotor is completely enclosed and shielded, both electrically and accoustically.

As stated earlier, either a 110-volt single phase or a 220-volt 3-phase motor

Film Editing Made Easy
with NEW
professional film viewer
for 35mm film

Every film editor will appreciate a viewer that enables him to view his film from left to right—on a large, brilliantly illuminated screen.

The PROFESSIONAL FILM VIEWER *makes film editing a breeze. Easy threading, portable, will not scratch film. Put this viewer between your rewinders and speed up your editing. Size of Viewing Screen 5¾ x 4¾.*

35mm Model $375

FRANK C. ZUCKER
CAMERA EQUIPMENT
1600 BROADWAY NEW YORK CITY

Write Dept. A 9 4

may be used interchangeably with the system. When operating from batteries, it is only necessary then to provide one or the other power system to handle the recorder. In the early stages of developing the Model S6, the company proposed using a "multi-duty" or AC/DC camera motor operating from a 24-volt battery source. Due to the extremely high cost of motors of that type and to the mechanical problems in adapting them to the wide variety of motion picture cameras in use today, the proposal was discarded in favor of the comparatively inexpensive 24-volt-DC-to-110-volt-AC vibrator inverter. This item of equipment weighs only 19 pounds and has ample capacity to power any 16mm camera motor along with the S6 transport system. It is adequately filtered so that it offers no objectional electrical noise. The recording and playback amplifiers plus the inverter altogether pull in the order of 4 amperes from the 24-volt battery, so that it is possible to operate for an average day of normal shooting without need for recharging.

In designing the 35mm camera drive, the company encountered a severe problem. Because the Mitchell NC and BNC cameras have long been standard equipment in Hollywood studios, cameramen have come to favor a 3-phase 220-volt drive motor. It offers the reserve power

Model 35-16C
SENSITESTER

★ IMMEDIATE DELIVERY
to the lab owners interested in—

QUALITY
EFFICIENCY
ECONOMY

- **DUAL MACHINE**
  1—Sensitometer
  2—Scene Tester
- **HIGHLY ACCURATE**
  Electronic timer unaffected by climatic changes
- **NEW TYPE LONG-LIFE**
  Cold Light Exposure Unit
- **WITHOUT ADDITIONAL EXPENSE** will match any printer

Combination 35mm-16mm

ART REEVES MOTION PICTURE EQUIP.
7512 Santa Monica Blvd.
Hollywood 46 **California**

necessary to drive the camera efficiently at low temperatures, and it is extremely quiet acoustically. But on location camera motors of this type generally require use of a sound truck, which has battery power sufficient to drive both the camera motor and the recording equipment, and this often limits portable operation and distant location shooting, which are important factors in film production today.

To overcome this, Stancil-Hoffman designed a rotary converter generating 230 volts of 3-phase current from a 24-volt storage battery. This provides sufficient output to drive a Mitchell camera motor along with the S6 recording system under any environmental conditions.

The converter, along with its control unit, also permits "undercranking" the camera, which is so important in many motion picture photographic assignments. The converter weighs 35 pounds and operates from the same 24-volt battery which powers the electronic section of the S6. It is acoustically quiet and does not create any electrical noise in the system. The control unit, also known as the camera control, operates from a remote position to stop and start the converter; it also sets the speed, as indicated by vibrating reeds, in any range between 16 and 26 f.p.s. The reeds are calibrated in half-frame increments, from 23 to 25 frames.

According to William Stancil, president of the company, in designing the S6 system, the company has endeavored to provide as accessories all cables, batteries, battery chargers, spare tube kits, microphones, sound powered telephones, plug-in audio oscillators necessary to field maintenance—everything that is required for a complete sound recording system.

"Our aim," he said, "has been to provide the film producer with a portable magnetic recording system that is sufficiently complete, compact, and efficient to enable him to accomplish the most difficult mobile or location shots."

SHOOTING MOVIES FROM THE AIR

(Continued from Page 541)

therefore in reducing the interval between exposed frames of the terrain. In addition it will give a shorter exposure time, or increased shutter speed. This more than compensates for the slightly more prolonged exposure where a larger shutter opening is used, and also results in a slow-motion effect which minimizes the effect of vibrations.

When filming from a plane the camera speed should be higher than normal. This reduces the interval between frames, gives a shorter exposure time, and slows down undesirable camera movement on the screen. Depending upon the speed and altitude of the plane, a shooting speed of 32 to 64 frames per second should be used to obtain normal effects in 24 f.p.s. projection. (24 to 48 frames per second for projection at 16 f.p.s.). As increasing altitude takes you farther from your subject, the camera speed may be reduced without inducing flicker on the screen. When filming from an extremely slow-moving aircraft, such as a helicopter or blimp, the normal camera speed may be quite acceptable, even for low altitudes.

Because of the forward speed and inherent vibration of most planes, it is not advisable to use long focal length lenses for aerial cinematography. On the other hand a wide-angle lens shouldn't be used either, because of it's tendency to exaggerate distances. As a general rule the normal angle lens will give the best results.

Where a camera with turret is being used, the lens caps should be removed from all lenses, otherwise they may be blown off and lost in the slip stream during flight.

The taking lens should be set at infinity focus and locked or taped in that position. Any other settings that might easily be knocked out of position should be taped in place.

Basic exposure calculations for aerial photography are essentially the same as those for ground photography. In other words, whatever, basic exposure you would use for a subject on the ground, use the same exposure for that shot from the air. Exposure allowances must be made for faster camera operating speeds and when using some haze-cutting filters. Where your target (subject) involves a large amount of surrounding foliage, allow for additional exposure. On the other hand, if confronted by large bodies of sand, water, snow or numerous puddles of rainwater, the additional reflectance will require stopping down exposure. In the air, exposure consideration must be given for sidelighting and backlighting, just as in ground photography. However, for aerial work, a greater hazard of overexposure exists for backlighted subjects surrounded by water because it casts back reflections of the sun.

When exposures are determined with a reflectance type exposure meter, readings should be taken on the ground before the take-off. Meter readings from the air pick up too much reflectance of haze and therefore tend to give a false reading. Where exposure conditions

The FINEST
400-Ft. CONVERSION
of Auricon Cine-Voice



Only $513 with your magazine
Hinged Door. Write for Details
Filmtronics, Inc.
Dept. A, 96 Huntington St., New London, Conn.



PORTABLE WATSON CINE DEVELOPING OUTFIT provides a SIMPLE, EFFICIENT, ECONOMICAL and SPEEDY means for PROCESSING up to 200 ft. of 16mm or 35mm (also 70mm) film—
- LOW COST Uniform Processing! Requires only 1 gal. of solution
- 3 reeling tanks-reels-scratch proof loader
- PREFERRED by MORE Professionals
- SIMPLE operation MINIMUM cost—
- FULLY GUARANTEED—prices from $95.00

Extra Reels Tanks etc., available
Write for FREE Processing Booklet Dept. AC
BURKE & JAMES, INC. 321 So. Wabash, Chicago 4

Automatic Daylight Processing

DEVELOPING TANK
- Processes up to 200 Ft.
- 8mm-16mm-35mm
- Movie—X-Ray—Microfilm
- Motor driven turntable
- Tough plastic tanks
- Uniform Density Assured
- 70mm tank also available

FILM DRYER
- Motor driven—Heated
- Speedy drying
- Automatic shrinkage allowance
- Stainless steel and aluminum construction
- Easily assembled without tools
- Compact Portable

Guaranteed Write for Free Literature
Micro Record Corp. Dept. AC 487 South Ave. Rochester, N. Y.

NOW! MOST ADVANCED REVERSAL ON MARKET FOR ONLY $2495!

AMAZING NEW PERFORMANCE PROVED BY ACTUAL OPERATION IN HUNDREDS OF CUSTOM FILMLINE INSTALLATIONS

- Processes reversal films at 900 ft per hour
- Handles negative and positive film at speeds up to 1000 ft per hour
- SIZE 76" x 48" x 24"
- WEIGHT 450 lbs crated
- PRICE $2495 F.O.B. Milford, Conn. Accessories additional

WRITE TODAY FOR FULL DETAILS AND LITERATURE

One of 12 standard models from $1095

Filmline

MODEL R15 REVERSAL FILM PROCESSOR FOR TV, INDUSTRY, COLLEGES—OTHERS

NEW DESIGN CONCEPT! Units removable for cleaning. Eliminates maintenance.

NEW SIMPLICITY OF OPERATION!

NEW EXCLUSIVE OVERDRIVE! Eliminates film breakage, slack buildup, automatically compensates for film elongation.

NEW COMPLETE DAYLIGHT OPERATION! No darkroom. Removable daylight magazine.

NEW QUALITY THROUGHOUT! Heavy gauge stainless steel tanks. Filtered air intake.

Filmline leads the field in engineering and manufacturing standard and custom 16- 35- 70MM b & w and color film processing machines of all types

Filmline corp. Dept. C, Milford, Conn.

DISTRIBUTORS: Camera Equipment Co., 1600 Broadway, New York, N. Y. • S. W. Caldwell, Ltd., 447 Jarvis St., Toronto, Canada

change while in flight, and you need to take meter readings, take a reading from the palm of your hand, with the hand facing the sun in the same relationship as the sun is to the "target."

Meter readings from a neutral "grey card" will be found more consistently reliable if you have already established that practice. In the plane meter readings should be taken with the sunlight coming through an open window to strike reflective surface. When possible shoot through an open window. If you must film through plexi-glass then it will be necessary to open up from a half to a full stop to allow for the loss of light transmission. A meter reading taken with the light source filtering through a plexi-glass window would discount the light loss in filming and will therefore read directly in the correct basic exposure. Don't forget, however, to open-up for a change in frames per second. (Doubling f.p.s. will require opening one f/ stop.) Also don't forget to open up additionally for the haze-cutting filter if one is used. (See the accompanying table on filters.) While air-borne, do not expect to get a reliable reading, from an incident-type meter, unless it is converted for reading reflected light. Where weather conditions are not changing rapidly, the best bet is to determine exposure and make all

(Continued on Page 555)

COMPLETE MOTION PICTURE EQUIPMENT

RENTALS

FROM ONE SOURCE

CAMERAS

MITCHELL
16mm
35mm Standard
35mm Hi-Speed
35mm NC • 35mm BNC

EELL & HOWELL
Standard • Eyemo • Filmo

ARRIFLEX
16mm • 35mm

WALL
35mm single system

ECLAIR CAMERETTE
35mm • 16/35mm Combination

AURICONS
all models single system
Cine Kodak Special
Mourer • Bolex
Blimps • Tripods

DOLLIES
Fearless Panoram
Cinemobile (CRAB)
Fluttarm • Western
3 Wheel Portable

LIGHTING

Mole Richardson
Berdwell McAlister
Colortran
Century
Cable
Spider Boxes
Bull Switches
Strong ARC-Trouper
10 Amps 110V AC 5000W-2000W-750W
CECO Cone Lites (shadowless lite)
Gator Clip Lites
Barn Doors
Diffusers
Dimmers
Reflectors

EDITING

Moviolas • Rewinders
Tables • Splicers
Viewers (CECO)

GRIP EQUIPMENT
Parallels • Ladders
2 Steps • Apple Boxes
Scrims • Flags
Gobo Stands
Complete grip equipment

SOUND EQUIPMENT
Magnasync magnetic Rim
Reeves Magicorder
Mole Richardson Booms and Perambulators

Portable Mike Booms
Portable Power Supplies to operate camera and recorder

WE SHIP VIA AIR, RAIL OR TRUCK

FRANK C. ZUCKER
CAMERA EQUIPMENT CO.
Dept. A-9-19 • 1600 Broadway • New York City

HOLLYWOOD STUDIO PRODUCTION

Feature and television film productions for which members of the American Society of Cinematographers were engaged as Directors of Photography during the past month.

AMERICAN SOCIETY OF CINEMATOGRAPHERS

●

ARTHUR MILLER, President
SOL HALPRIN, First Vice-President
WILLIAM SKALL, Second Vice-President
ALFRED GILKS, Third Vice-President
WALTER STRENGE, Treasurer
CHARLES G. CLARKE, Secretary
ROBERT DE GRASSE, Sergeant-At-Arms

BOARD OF GOVERNORS

JOSEPH BIROC
GEORGE FOLSEY
BURNETT GUFFEY
WINTON HOCH
HAL MOHR
RAY RENNAHAN
LEON SHAMROY
PHILIP TANNURA

ALLIED ARTISTS

● ELLSWORTH FREDERICKS, "World Without End," (Color; CinemaScope) with Hugh Marlowe, Nancy Gates, Lisa Montell, Shawn Smith. Edward Bernds, director.

● FLOYD CROSBY, "Shack Up On 101," (Retitled "Girl on 101") with Terry Moore, Frank Lovejoy, Keenan Wynn, Lee Marvin, Edward Dein, director.

● ELLSWORTH FREDERICKS, "Calculated Risk," with Bill Elliott, Beverly Garland, Tom Drake, Helene Stanton, Hubert Cornfield, director.

COLUMBIA

● RAY JUNE, "Tambourine," (Technicolor, CinemaScope) with Jane Russell, Cornel Wilde, Luther Adler, Joseph Calleia, James Russell. Nicholas Ray, director.

● CHARLES LAWTON, "Jubal Troop," (Technicolor; CinemaScope) with Glenn Ford, Ernst Bergmne, Rod Steiger, Valerie French, Felicia Farr, Basil Ruysdael, Noah Berry Jr., Delmer Daves, director.

● HARRAY STRADLING, "The Eddie Duchin Story," (Technicolor, CinemaScope) with Tyrone Power, Kim Novak, James Whitmore, Rex Thompson George Sidney, director.

METRO-GOLDWYN-MAYER

● ARTHUR ARLING, "I'll Cry Tomorrow," with Susan Hayward, Richard Conte, Eddie Albert, Don Taylor, Jo Van Fleet. Daniel Mann, director.

● RUSSELL HARLAN, "The Last Hunt," (Eastman Color; CinemaScope) with Robert Taylor, Stewart Granger, Lloyd Nolan. Richard Brooks, director.

● ROBERT SURTEES, "Tribute To A Bad Man," (Eastman Color; CinemaScope) with James Cagney, Stephen McNally, Irene Papas, Don Dubbins Robert Wise, director

PARAMOUNT

● LOYAL GRIGGS, WALLACE KELLEY, PEVERELL MARLEY, "The Ten Commandments," (VistaVision, Technicolor), with Charlton Heston, Anne Baxter, Yul Brynner, et al. Cecil B. De Mille, director.

● DANIEL FAPP, "The Birds and the Bees," (Technicolor, VistaVision), with George Gobel, Mitzi Geynor Norman Taurog, director.

R.K.O.-RADIO

● WILLIAM SNYDER, "Great Day In The Morning," (Technocolor, Superscope) with Robert Stack, Virginia Maye, Ruth Roman, Alex Nicol, Raymond Burr Jacques Tourneur, director

TWENTIETH CENTURY-FOX

● LEON SHAMROY, "Good Morning, Miss Dove," (Color, CinemaScope) with Jennifer Jones, Robert Stack, Kipp Hamilton, Robert Douglas, Peggy Knudson, Biff Elliott, Mary Wickes, Chuck Connors. Henry Koster, director.

● MILTON KRASNER, "Rains of Ranchipur," (Color, CinemaSope) with Lana Turner, Richard Burton, Fred MacMurray, Joan Caulfield, Michael Rennie, Paul H. Frees. Jean Negulesco, director.

● CHARLES CLARKE, "Carousel," (Color; CinemaScope) with Frank Sinatra, Shirley Jones, Barbara Ruick, Cameron Mitchell, Claramae Turner, Audrie Christie, Robert Rounseville. Henry King, director

● LEO TOVER, "The Lieutenant Wore Skirts," (Color, CinemaScope) with Tom Ewell, Sheree North, Les Tremayne. Frank Tashlin, director

UNIVERSAL-INTERNATIONAL

● ELLIS CARTER, "A Day of Fury," (Technicolor), with Dale Robertson, Jock Mahoney. Harmon Jones, director.

● WILLIAM DANIELS, "The Benny Goodman Story," (Technicolor) with Steve Allen, Donna Reed, Berta Garsten, Barry Treux, Harry James, Ben Pollack, Gene Kruppa, Lionel Hampton, Teddy Wilson. Valentine Davies, director

● ELLIS CARTER, "A Day of Fury," (Technicolor) with Dale Robertson, Mara Corday, Jock Mahooey, Carl Benton Reid, Jan Merlin, John Dehner Harmon Jones, director.

● JACK RUSSELL, "Law Man," (Technicolor) with John Agar, Mamie Van Doren, Richard Boone, Leif Erickson, Coleen Gray. Charles Haas, Director.

● HAROLD LIPSTEIN, "Pillars in the Sky," (Technicolor, CinemaScope) with Jeff Chandler, Dorothy Malone, Keith Andes, Ward Bond. George Marshall, director.

● MAURY GERTSMAN, "The Creature Walks Among Us," with Jeff Morrow, Rex. Reason, Leigh Snowden, Gregg Palmer John Sherwood, director.

WARNER BROTHERS

● WILLIAM MELLOR, "Giant," (Warnercolor) with Elizabeth Taylor, Rock Hudson, James Dean, Jane Withers. George Stevens, director.

● SAM LEAVITT, "The Court-Martial of Billy Mitchell," (Wornercolor, CinemaScope), with Gary Cooper, Ralph Bellamy, Fred Clark, Herbert Heyes. Otto Preminger, director.

● EDWIN DUPAR, "The Lone Ranger," (Warner-Color) with Clayton Moore, Jay Silverheels, Bonita Granville, Lyle Bettger, Robert Wilke, Perry Lopez, and Michael Ansara Stuart Heisler, director

● TED MCCORD, TOM TUTWILER, "The Spirit of St. Louis," (Warner Color, CinemaScope) with James Stewart Billy Wilder, director

INDEPENDENT

● WINTON HOCH, "The Searchers," (C. V. Whitney Pics., Color, VistaVision) with John Wayne, Jeff Hunter, Vera Miles, Ward Bond, Natalie Wood, Lana Lisa Wood. John Ford, director

● GUY ROE, "Six Gun Lady," (Lyon & Bartlett Prods.) with Peggie Castle, William Talman, Marie Windsor, Bob Lowery, Joe Besser, Ian MacDonald, Earl Lyon Richard Bartlett, director.

● KARL STRUSS, "Mohawk,' (Eastman Color; Wide-screen, for 20th Century-Fox release) with Scott Brady, Rita Gam, Neville Brand, Lori Nelson Kurt Neumann, director

● LUCIEN BALLARD, "The Killer Is Loose," (Crown Prods.) with Joseph Cotten, Rhonda Fleming, Wendell Corey, Michael Pate, Alan Hale Budd Boetticher, director.

● LIONEL LINDON, "Around the World in 80 Days," (Michael Todd Prods., Todd-A-O) with David Niven, Cantinflas, Luis Dorninguin.

TELEVISION

(The following directors of photography were active last month in photographing films for television in Hollywood, or were on contract to direct the photography of television films for the producers named.)

ALAN STENSVOLD, "Dr Hudson's Secret Journal," (Authors); "Andya Gang," (Ferrin).

KENNETH PEACH, "Steve Donovan, Western Marshall," (Chertok); "Fury," (TPA)

KARL FREUND, "December Bride," (Desilu), "The Jimmy Durante Show," (Fawn-Desilu).

NICK MUSURACA, "The Lineup," (Desilu).

SID HICKOX, "My Favorite Husband," (CBS-Desilu).

ROBERT DEGRASSE, "Make Room for Daddy," (Marterto-Desilu); "It's Always Jan," (Jan ard-Desilu).

HAROLD WELLMAN, "Wyatt Erp," (616-Desilu).

WALTER STRENGE, "The Way," (Family).

VIRGIL MILLER, "You Bet Your Life," (Filmcraft).

ERNEST MILLER, "Gunsmoke," (Filmaster).

WILLIAM BRADFORD, Flying A Prodns.

LESTER WHITE, "Navy Log," (Gallu).

MACK STENGLER, "Ina Ray Hutton Show," and "It's Fun To Reduce," (Guild)

NORBERT BRODINE, "The Loretta Young Show," (Lewislor).

STUART THOMPSON, "Lassie," (Maxwell).

GEORGE E. CLEMENS, "Schlitz Playhouse of Stars," (Meridian).

HENRY SHARP, "Sheena, Queen of the Jungle," (Nassour).

JACK MCKENZIE, "Frontier," (Outpost).

LUCIEN ANDRIOT, "It's a Great Life," (Radie).

ED FITZGERALD, "You Are There," (Roach).

LOTHROP WORTH, "The Great Gildersleeve," (Roach).

GILBERT WARRENTON, "Sergeant Preston of the Yukon," (Skinner).

LLOYD AHERN, "My Friend Flicka," (TCF).

GUY ROE, "Gangbusters," (Visual).

CARL GUTORIE, "Cheyenne," and King's Row," (Worners)

HAROLD STINE, "Casablanca," (Warners)

JOE BIROC, "This Earth . . . This Land," (Town & Country).

SHOOTING MOVIES FROM THE AIR

(Continued from Page 553)

lens settings before leaving the ground.

At higher altitudes, aerial haze becomes a problem. Methods of counteracting this haze will vary, depending on whether color or black-and-white film is being used. First, consider the use of haze-cutting filters for black-and-white film. The higher the altitude, the more harmful is the effect of haze, and, accordingly, the denser your filter will be. Exposure, therefore, will also vary according to the filter used.

Aerial views from high altitudes are often veiled by water vapor in the atmosphere, though this is not always visible to the eye. If the haze is visible it will appear bluish, and is not to be confused with smoke, dust, or fog. Smoke and dust are solid particles. Fog is made up of millions of tiny water particles (not water vapor) and these particles cannot be penetrated by the use of haze cutting filters.

Haze has the effect of reflecting and scattering light of the shorter wave lengths (ultra-violet and blue light). Since all black-and-white films are sensitive to light of the shorter wave lengths, this extremely actinic light (full of radiant energy) will be recorded to produce a milky appearing veil over the scene if no filter is used. The veiling of the image becomes more pronounced as altitude of the plane is increased, or if the plane-to-target distance is increased as in high obliques.

The following table indicates the filters recommended for use with panchromatic film under various atmospheric conditions, and at different altitudes. Filter factors are included in parenthesis. Personal experience may suggest some variations from this table, particularly in the more arid region, where aerial haze is much less of a problem.

Color aerial photography does not permit a wide selection of haze-cutting filters. The amateur cinematographer may wish to use a U.V. filter in conjunction with Daylight Kodachrome. The Type A conversion filter (Wratten #85) used with Type A Kodachrome screens out much of the haze and gives very satisfactory results.

Framing for aerial movies is much the same as for ground coverage. Keep the subject as nearly centered as possible or a little above center. In low obliques and verticals the horizon will not show at all. In high obliques let the horizon come where it may, so long as the target is fairly well centered. Avoid including any more than a small portion of wings, struts, propellers, or engine nacelles. Do not allow the window edges to cut off any of your image. When filming from a multi-engined plane, avoid shooting through the exhaust stream, otherwise the screened image will be wavy, distorted, or blurred.

You rarely will be able to shoot in basic sequence from the air. Nevertheless try to film your subject from three different altitudes whenever possible, so that in editing, it can be cut for basic sequence, if desired.

END

FILTERS FOR BLACK AND WHITE AERIAL MOTION PICTURE PHOTOGRAPHY

	Altitude	Relatively No Haze (Very low humidity)	Light Haze (Moderate Humidity)	Heavy Haze may appear bluish (High Humidity)
Low Obliques and Verticals	Below 1000 feet	No Filter	K-2 (2x) light yellow	G (3x) deep yellow
	1000-2000 feet	No Filter	G (3x)	A-25 (8x)
	2660-5000 feet	No Filter	G (3x)	light red A-25 (8x)
	5000 10,000 feet	K-2 (2x)	A-25 (8x)	deep red or *Infra-red
	Above 10,000 feet	G (3x)	A 25 (8x)	deep red or *Infra-red
High Obliques (including horizon)	Below 2000 feet	K-2 (2x)	G (3x)	A 25 (8x)
	Above 2000 feet	G (3x)	A 25 (8x)	deep red or *Infra-red

*Used with Infra-red film
(2X=opening one f/stop)
(3X=opening one and one-half stops)
(8X=opening three f/stops)

Video Film Laboratories

is now located at

350 West 50th Street

New York 19, N. Y.

TELEPHONE: JUdson 6-7196

★

Complete 16mm laboratory service for Producers using the Revarsol Process

Also 16mm Negative and Positive developing.

★

WRITE FOR PRICE LIST

Established 1949

It's easy with the

MERCER FILM PATCH

Descriptive Chart & Price List Mailed on Request

R. C. MERCER & COMPANY

4241 Normal Ave., Holywood 29, Calif

NOrmandy 3-9331

Reversal

PROCESSING

Reversal specialists for over a decade. Our long experience assures superior quality. Electronically controlled machines keep temperature constant within .2 of one degree. National Brilliantone Cine prints are the finest available. Write for free catalogue.

CONTACT PRINTING — B & W DUPLICATING
WORK PRINTS — KODACHROME DUPLICATING
EDGE NUMBERING — VACUUMATING

All work reported at no extra charge

NATIONAL CINE LAB

Box 4425 Washington 17 D C

GEO W COLBURN LABORATORY INC.
184 NORTH WACKER DRIVE • CHICAGO 6
TELEPHONE STATE 2-7318
8 and 16mm
SERVICES

Ready-Eddy
U. S. Registered Trademark
FIFTH YEAR — USEFULNESS ACCLAIMED BY THOUSANDS
1001 Ready Sound-Film Editing Data:
• Footage • Frame Count • Screen Time • 35mm and 16mm equivalents
Plastic computer for everyone in movies and TV, from script to screen
$2.00 Prepaid
(Delivered to U.S.A.)
ASK FOR REPRINT OF ARTICLE IN AMERICAN CINEMATOGRAPHER
Write or ask your dealer
READY-EDDY, Sandy Hook, Conn.

SQUEEGEE TROUBLES?
Want a sure cure?
Try our low pressure squeegee unit
We guarantee results or your money back
Squeegee only with mounting bracket — $ 58.00
Packaged unit—squeegee, blower and hose — $110.00
METAL MASTERS
5599 University Ave., San Diego, Calif.

YOU WON'T MISS AN ISSUE . . .
of American Cinematographer if you renew your subscription promptly when notice is received. The yearly subscription rate remains the same — $3.00 (U.S. and Canada) Foreign, $4.00

FILMING A PRIZE-WINNER

(Continued from Page 538)

move indoors if the sky should become overcast.

Ruffner took special pains to keep the lighting at the same level in his indoor shots, so that the scenes would match when they were edited. He accomplished his purpose by moving his lights closer or farther from his subjects rather than by adding to or subtracting from the number of units used. Notes on exposure were made after each shot so that corrections could be made, if retakes were necessary.

Another practice which Ruffner found to be invaluable was the projection on his film viewer of scenes shot on the previous weekends. By using this technique, which he borrowed from professionals, Ruffner could compose and light his shots so that they would fit smoothly with those already taken.

While filming the indoor scenes, Ruffner discovered that his 15mm lens did not possess a wide enough angle. He was obliged to buy a 13mm lens which enabled him to take the necessary shots in the cramped quarters.

Because the indoor shooting was carried on at intervals of two or three weeks, meticulous notes were kept. Such seemingly trivial items as the position of a plate on the dining-room table and the number and shape of Geraniums in a vase were recorded for further reference.

While Ruffner was solving his photographic problems, the actors had their own difficulties with which to contend. Mrs. Osenda had to forego a permanent for several months. Her hair had to appear the same in shots taken weeks apart. Thus, it could not be changed.

The family was forced to store new furniture purchased during the shooting of the picture. The heavy articles would have been too difficult to move in and out of the house for a day or two of movie making each week.

"Complete cooperation is imperative in amateur productions," Ruffner said. "Everyone has to agree from the start to carry the work through to completion in spite of the sacrifices which each will have to make. Without such understanding an amateur film is doomed to failure before it is begun."

Authenticity of appearance gave Les Thomson, who played the blind man, several amusing moments. During the shooting on the streets of Sunnyvale, an elderly woman did not see the camera and mistook Thomson for a real blind person. She paused, took a coin from her purse and dropped it into the hat he was holding. The lady walked on without realizing that he was an amateur actor. Thompson later gave the money to a deserving cripple.

Osenda continually was kidded by fellow workmen at the firm where he and Ruffner are employed. Each Thursday he had to stop shaving so that his beard would be the right length for weekend movie making. His beard and clothing were convincing enough to fool a group of real hoboes.

"We accidentally discovered a hobo jungle when we were scouting locations and decided to try to use the men who stayed there in our production," Ruffner explained. "When we were ready to shoot, Eric approachd the men while we stayed out of sight. At first they thought he was one of their kind and offered him some food. He told them, however, that he was one of a group of amateur movie makers who wanted them to act in a picture. They agreed and we moved in with our equipment."

While he was shooting sequences in the hobo jungle, Ruffner made one scene which has brought praise wherever the picture has been shown. It shows the hobo imagining how he would appear in a new suit of clothes. Osenda first appears in his hobo costume and through the use of a lap dissolve he is shown in his imagined finery. Then a lap dissolve is made back to the previous shot.

Work on this scene was so skillfully executed that persons not acquainted with motion picture techniques wonder how it was done. Experienced photographers admit it is one of the best lap-dissolve sequences that they have seen.

Throughout the scene Osenda's pose alters only slightly, in spite of the fact that he had to move between takes to make costume changes. Near perfection was accomplished through the use of diagrams, copious notes and careful markings on the log on which Osenda was sitting. Ruffner's careful planning paid off. The scene was successful on the first attempt.

At a railroad yard, where the opening and closing sequences of the film were shot, the group met a man who had been a bit player in professional motion pictures. He was interested in their picture and introduced them to the yard master.

"Through the cooperation of the two men," Ruffner said, "I was able to shoot scenes which would have been difficult to obtain otherwise. The yard master held up switching several times so that we could get the shots we needed."

After the shooting of the picture was completed, Ruffner and his wife still

(Continued on Page 558)

CLASSIFIED ADVERTISING

RATES: *Ads set in lightface type, 10c per word; minimum ad, $1.00. Text set in lightface capital letters (except 1st word and advertiser's name) 15c per word. Modified display format (text set in boldface type, capitals or upper and lower case) 90c per line. Send copy with remittance to cover payment to Editorial Office, American Cinematographer, 1782 No. Orange Drive, Hollywood 28, Calif. Forms close 15th of month preceding date of issue. No discount on Classified Advertising.*

STUDIO & PRODN. EQUIP.

SHOP AT THR ONR STOP SHOP

ANIMATION STAND COMPLFTE for 16mm compound table with 360° rotation; N-S-E-W Acme sliding pegbars; 4" to 12" field; platen, Vendor counters; shadow box; circline lightbox and art table ..... $2500 value $1295.00

HOUSTON FEARLESS PERAMBULATOR DOLLY, $2100 value 1350.00

TIME LAPSE INTERVAL Meters for Bolex and Cine Special, complete 146.00

AKELEY AUDIO SOUND CAMERA 6 focal lenses 3 magazines; motor; V-D governameter; amplifier; 2 WE mikes; cables and cases. $9500 value 4450.00

AKELEY 35mm EDITING MACHINE, sound, picture preview, $3000 val..... 1295.00

NEW FRESNEL STUDIO SPOTS, lead wires, switch pipe clamp
2000 Watt..... $59.95 5000 Watt 99.95

NEW 1500W NEWSREEL FLOODLITES, $100 value. Close out 29.50

NEW ENCLOSED FILM STORAGE CABINETS, capacity 20—400' reels, 2 drawers.. grey enamelled $37.50 value. 14.95
Lots of 3.....$12.95 Lots of 6..... 9.95

HARDWELL McALISTER MULTIPLE FLOODLITES, 3 Quadruple heads to hold 12 bulbs on rolling tripod stand. Orig Govt cost $180. Surplus 29.50

BM QUADLITE Heads only $4.95. Stands only 19.95

B&H 16mm FILMO SPECIALIST CAMERA w/tackover, matte box, Mitchell type finder, synchrotor 400' mag w/case $2000 value 995.00

CUSTOM BLIMP for B&H 70D with sync motor 195.00

EASTMAN AIRGRAPH 16/35mm FILM DEVELOPING MACHINES. Fixes washes, dries. Stainless steel tank and drum, drive motor, heater, blower. $1800 value. Govt surplus 295.00

DUAL REKOKUT TRANSCRIPTION TURNTABLES with Grey 16" pickups, on cabinet pedestal, $500 value 225.00

BRIDGAMATIC 16mm PROCESSOR for negative/positive, w/refrigeration, air pump; feed-in and take up elevators, speed up to 1800' per hr. Good as is, $4700 value. 1795.00

CINEX EXPOSURE TESTING MACHINES—used by labs. Originally $4000.00. Rebuilt ... 1995.00

ART REEVES 35mm OPTICAL SOUND RECORDER; interlock motors; footage counter tachometer; ultra violet glowlamp amplifier; double mixer, $5,000 value. Close out 495.00

RCA Type 6 CHANNEL MIXER w/power supply. $2000 value. 495.00

BERNDT MAURER CAMERA w/finder 3 lenses 4—400' magazines, sunshade, 12V motor; synchrotor, varispeed motor with tachometer; Mitchell tripod. $4000 value. 2495.00

STEEL SPARE PARTS CASES—20 compartments to hold lenses, filters, tubes, mikes, lamps etc. Felt lined with handle. 7"x12"x17" Govt Surplus 9.95
6 for $3.00. ..... 12 for $5.00

AURICON DOUBLE SYSTEM RECORDER w/noise reduction amplifier 295.00

TRADES TAKRN Cable SOSOUND Dept fc
S O S CINEMA SUPPLY CORPORATION
602 W 52nd Street, New York 19 Phone PL 7-0440

I YEAR OLD & STILL GROWING
HOLLYWOOD'S NRWEST STORR

Cine Special II 200' mag. FI 4 EKTAR perfect ..... $ 749.50
Auricon Pro complete 949.50
Parrish 400' Auricon 949.50
Cineflex 35 Camera 495.00
B&H 70DA—3 lenses 295.00
Reeves Sensitester 425.00
B&H Meters Mod 70 or 71 ..... 92.50
Moviola 16mm Previe Mod 1250.00
Mitchell Baby Tripod 42.50
Nat Cine Dolly, used 239.50
Griswold 16mm Splicer, new 14.95
B&H Specialist with Stop Motion Rackover, Feder built in, with four lenses in turret 1495.00
Norwood Meter, new 26.50
Eyemo Single Lens Mod 249.50
O'Connor Fluid Head 16mm 260.00
Pro Jr Tripod used 99.50
Cinekad Dolly 85.00
Many other items new & used
Trades invited—Try us
LLOYD'S CAMERA EXCHANGE
1614 Cahuenga Blvd.
Hollywood, Calif

STUDIO & PRODUCTION EQUIPMENT

CINE Special camera, four lens turret; Mauer B&M upright image viewfinder; matte box and sunshade. $625.00. Auricon pro 16mm camera with Kinescope shutter, variable density galvo & amplifier, cannon plugs; mike complete. Almost new condition, $995.00. MOTION PICTURE SERVICE STUDIO, 328 North 11th Way, Phoenix, Arizona. AL 4-0125.

FOR SALE

BASS ... is headquarters for Auriflex 16 the new Zeemar 16 Cine specials all models Bell & Howell 70 DL; Bolex H-16 L.N. Cine Special II. 1" F:1.4 15mm F:2.5 Ektars optical finder reflex finder extra 100 ft chamber Yale feder, case, $2020.00 value for $1075.00. Cine Special I, 1" F:1.9, 3" F:3.5, $395.00; B&H 70DA 1" F:1.8, 15mm F:2.5, 3½" F3.3 Cookes $245.00. N16 DeLuxe Bolex, 1" F:1.9 16mm F:2.8, 3" F:2.8 Comb Case $375.00. Victor 5, 1" F:1.5, 3" F:3.5 $135.00. Best buys. Best trades always. BASS CAMERA CO. Dept AC 179 W Madison St. Chicago 2, Ill.

GSPA 16mm MAGAZINF CAMFRA, f3.5 as is.. $ 24.95
PATHE 16mm LATEST MODEL 279.50
BOLEX PAN CINOR ZOOM LFNS 199.50
KD 8mm ACTION VIEWER 14.95
BOLEX STEREO OUTFIT, COMPLETE 99.50
CRAIG EDITING OUTFIT, 8 or 16 mm, complete 59.50
CRAIG 8mm VIEWER only (old model) 27.50
FOCUSING FINDERS, Bell and Howell 16mm, Revere 16, Kodak 8 or 16—your choice. ... 17.50
Mail orders promptly filled
CAMERA CRAFT
18 E 42nd St., New York 17, N.Y.

WE ALWAYS HAVE BARGAINS
In Professional 35 & 16mm equipment
CAMERAS — LIGHTS
MAGNETIC and OPTICAL
RECORDERS and PLAYBACKS
MOVIOLAS — DOLLYS — BOOMS
Send for our constantly changing list
Hundreds of Other Production Items.
Write — Wire — Phone
CINEMA SERVICE CORP.
706 West End Avenue, New York 23, N.Y.
TRafalgar 3-1411

AUDIO AKELEY single system camera complete with Akeley sound head, Gyro tripod, 3 lenses, view finder, Maurer mixing amplifier. Complete with cables, power supply and W E microphone. CAMERA EQUIPMENT CO 1600 Broadway New York 19 N Y Cable: Cinequip

WALL B. S. 35MM SOUND CAMERA
COMPLETE with Galvanometer amplifier portable power supply, 40-50-75 and 100mm. lenses, erect image viewfinder complete front attachments two 1000 ft magazines. Balanced Tripod, necessary carrying cases. Overhauled. Guaranteed perfect. Reasonable.
CAMERA EQUIPMENT COMPANY
1600 Broadway New York 19, N. Y.

PRECISION Magnetic Heads for Engineers - Industry
Erase - Record - Playback
STANCIL-HOFFMAN CORPORATION
921 North Highland Avenue
Hollywood 38, California

CAMERAS, 35mm recording single frame, 100' capacity, Mfg St George original cost approximately $600.00. Complete less lens used $12.50, new $150.00. Cash with order. Shipping weight approx 14 lbs. J WALTON, P O Box 1457 Tampa Florida

MAGNASYNC—16mm magnetic recorder model SW 602-RE, used only two months. INTERNATIONAL MARKETERS. 2432 Iowa, Cincinnati, Ohio.

BRIDGAMATIC 16mm negative positive machine rebuilt to do 1200 ft positive per hour. $850.00. MASTER FILM, 207 Third St. Elizabeth N.J.

AURICON Pro CM71 and EIF View Finder, cases and related equipment barely used. Write R FAITH, 585 N Winter Street, Salem, Oregon

FOR SALE

GERMAN STILL 35mm cameras. Import your own. Save Importers and retailers profits. (About 35%.) Pay postman duties. Examples: EXAKTA. The only completely versatile 35mm camera. With:
Automatic diaph. Zeiss Tessar
F/2.8 ..... $159 (duty $22.)
Automatic diaph. Isco Westener
F/2.8 ..... $139 (duty $19.)
Automatic diaph. Schneider Xenon
F/1.9 ..... $195 (duty $26)
Automatic diaph. Zeiss Biotar
F/2.0 ..... $199 (duty $26)
Similar prices all other famous makes. All new. Latest 1955 production in original factory packing. Parcelpost and insurance included. No other charges. Pre payment through bank and inspection on arrival guarantees you complete satisfaction before we are paid. Experienced, (and objective) advisory service (please specify interests and requirements) and proclaim by return airmail. All transactions on money back basis. WORLDPOST TANGIER, MOROCCO

Bell & Howell Cameras with rackovers
Used gear and friction head tripods
Mitchell, B&H or barrel mounted enses—any focal length any brand
Used mike boom, wheeled, lightweight
Used 3 wheel dolly with seat sturdy
Single sprocket 35mm film counters
Used Mitchell upright viewfinders
Single lens and turret Eyemos
Molded Plastic Film Rollers
Processing machine parts
Arriflex cameras.
Projectors
PRODUCTION & TEST EQUIPMENT
MACHINE AND CAMERA PARTS
Always thousands of items in stock
Prices and true statement of condition always cheerfully given
ART REEVES MOTION PICTURE EQUIPMENT AND CAMERA SUPPLY CO
7512 Santa Monica Blvd., Hollywood 46, Calif.

16MM HOUSTON K I A . . . developing machines. For reversal or positive film. Complete with refrigerator units temperature control, condensers, evaporators, thermostats, etc. BRAND-NEW, prices reduced! Write AIB PHOTO SUPPLY, Dept C-1, 555 E. Tremont Ave., New York 57 New York.

WE BUY, SELL AND RENT PROFESSIONAL AND 16mm EQUIPMENT, NEW AND USED. WE ARE DISTRIBUTORS FOR ALL LEADING MANUFACTURERS. RUBY CAMERA EXCHANGE, 729 Seventh Ave., New York City. Established since 1910.

MOVIOLAS—composite and regular magnetic and optical sound projection picture. CINEMA RENTALS COMPANY, 139C North Beachwood Drive, Burbank, California. Thornwall 9-8953.

WANTED

SELL US WHAT YOU'VR GOT
Cameras, Dollies, Lenses, Lights, Moviolas, Printers, Recorders, Studio or Laboratory Equipment
We also trade or take consignments. Set your own price—we'll get it.
Western Union-WUX New York, Phone PL 7-0440
S O S CINRMA SUPPLY CORPORATION
Dept fc Cable: SOSOUND
602 W 52nd Street New York 19, N Y

IMMRDIATE CASH PAYMRNT FOR CAMRRAS AND EQUIPMRNT
NEED EYEMOS (SINGLE LENS AND TURRET) MITCHELLS ARRIFLEX DE DRIES, B&H STANDARDS AND HI-SPEEDS, WALLS, AKELEYS, CINE SPECIALS, AURICONS, MAURERS, FILMOS. ALSO BALTARS, COOKES AND OTHER LENSES. SOUND STAGE LABORATORY AND EDITING EQUIPMENT OF ALL TYPES REQUIRED. PLEASE SHIP INSURED OR FORWARD DESCRIPTIONS AIRMAIL. IMMEDIATE PAYMENT.
GORDON ENTRRPRISES • 5363 N. Cahuenga
NORTH HOLLYWOOD, CALIFORNIA

(Continued on Next Page)

Classified Ads

(Continued from Preceding Page)

WANTED

WANTED TO BUY FOR CASH
CAMERAS AND ACCESSORIES
MITCHELL, R & N, EYEMO DEBRIE AKELEY ALSO
LABORATORY AND CUTTING ROOM EQUIPMENT
CAMERA EQUIPMENT COMPANY
1600 BROADWAY, NEW YORK CITY 19
CARLE CINEQUIP

WANTED FOR SPOT CASH
Used Mitchells, Auricons—other Cameras
Moviolas—Editing Equipment—Projectors
Spotlights—Sound Equipment

All Types Used Equipment
From a Splicer to a Complete Studio

Write—Wire—Phone
or Send Equipment in for Spot Cash

FLORMAN & BABB Murray Hill 2-2928
68 West 45th Street New York 36, New York

WANTED
Mitchell — Akeley — R & H — Wall — Eyemo
Cameras — Lenses — Equipment
NATIONAL CINE EQUIPMENT, INC
209 West 48th St New York, N Y

WANTED
PRODUCTION EQUIPMENT, LABORATORY EQUIPMENT, EDITING EQUIPMENT, 16mm and 35mm FROM SINGLE ITEMS TO COMPLETE STUDIOS TRADES ACCEPTED
THE CAMERA MART, INC
1845 Broadway Circle 6-0930 New York 23, N-Y

F & B PAYS MORE
FOR USED 16/35MM EQUIPMENT
WRITE — WIRE — PHONE
FOR OUR CASH OFFER
FLORMAN & BABB MU 2-2928
70 W 45TH ST NEW YORK 36, N Y

POSITIONS WANTED

NEGRO—Catholic, experienced cameraman, 35mm newsreel, 16mm color productions editing, lighting, titling, also projectionist MALCOLM MYERS 3424 Clark Ave St Louis 3 Missouri.

CAMERA and recording team, two young men, excellent background experienced in 16mm color productions, editing and titling Can supply own equipment Box 121R, American Cinematographer

YOUNG man excellent background experienced in 16mm camera work, editing titling and recording Box 1219 American Cinematographer

CAMERAMAN writer editor Six years university, expedition experience Single Write for resume. RICHMOND LAWRENCE, 10 Collamer Road Hilton, New York

PERMANENT position wanted by 16mm cameraman familiar with all phases of industrial production Write BOX 1220, American Cinematographer

ASSIGNMENTS WANTED

CAMERAMAN writer editor experienced cinematographer have traveled throughout the USA on assignments Will take overseas duty, underwater etc. Can also edit prepare scripts direct College background young 35 Full particulars write BOX 1217 American Cinematographer

ALASKA assignments 16mm sound or silent 35mm silent DON CUTTER 23R 4th Avenue Anchorage, Alaska

LABORATORY & SOUND

LABORATORY Services 16mm 35mm Developing, Printing & Reduction Reasonable Quality guaranteed NATIONAL FILM PRODUCTIONS 955 Diana Ave, Akron, Ohio

LABORATORY & SOUND

ROCKY MOUNTAIN 16MM HEADQUARTERS
Processing — Printing — Recording
Editing — Production — Rental — Sales
DuPont, Eastman and Fuotax films in stock
Write for Price List
WESTERN CINE SERVICE, INC.
114 E. 8th Ave., Denver 3 Colo TAbor 5-2812

SOUND RECORDING at a reasonable cost High Fidelity 16 or 35 Quality guaranteed Complete studio and laboratory services Color printing and lacquer coating ESCAR MOTION PICTURE SERVICE, INC., 7315 Carnegie Avenue, Cleveland 3 Ohio Phone Endicott 1-2707

PRINTING! REASONABLE PRICES! FREE ESTIMATES! Sebastian 10934-C Nemlin, North Hollywood, Calif

16mm SOUND and picture editing—sound recording—music—effects DON DUNN'S EL RANCHO AUDIO, near Palos Verdes and L.A. Harbor 26246 Fairview Avenue Lomita, Calif DAvenport 6-4925

Here on this page you'll find two outstanding opportunities

. . . 1—To buy an item of much needed equipment at an attractive price,

. . . 2—Opportunity to dispose of items you no longer need; to sell your services; or to make known your needs in our "wanted" columns.

Classified advertising rates are surprisingly low.

Just 10c a word when your ad is set like this·

AURICON Pro CM71 and EIF View Finder, cases and related equipment barely used.

Or 15c per word when text is set in all capitals, like this·

PRODUCTION EQUIPMENT, LABORATORY EQUIPMENT, EDITING EQUIPMENT, 16mm

Or 90c per line when text is set in boldface, like this· (Note This style is limited to headline and signoture lines only.)

1 YEAR OLD & STILL GOING
HOLLYWOOD'S NEWEST STORE

Send ad copy accompanied by remittance to cover payment to American Cinematographer, 1782 No. Orange Drive, Hollywood 28, Calif. Closing date for copy is 15th of month preceding issue date.

FILMING A PRIZE-WINNER

(Continued from Page 556)

had many hours of work ahead of them. One month of spare time was spent in the five editings of the film.

"Many times Harry would remove only two or three frames from a scene," Mrs Ruffner said. "We had to make certain that the movement of a band, for example, would run smoothly from shot to shot."

Mrs. Osenda band lettered the titles for the picture on a long strip of black paper. Ruffner then shot these twice at different exposures on the scroll attachment of his homemade titler. He rewound the film and shot backgrounds of a moving train on the same film at Gold Run in the Sierra Neveda mountains. Of the two titles that Ruffner made, the second proved to be most satisfactory.

While the edited film was being prepared at a laboratory for magnetic sound recording, Ruffner selected background music and wrote three short bits of narration. The background music was recorded on his own recorder and the sound from the tape was fed into his magnetic sound projector as the narration was being read. Sal Pizzo, a San Francisco resident experienced in amateur theatricals, was narrator.

The Ruffners, members of the Westwood Camera Club of San Francisco, shot their film on single perforated Type A Kodachrome with a Cine Kodak-Special. Daylight conversion filters were used for the outdoor work. Lenses used were a 15mm f/2.7, a 13mm f/1.5 and a 25mm f/1.9.

Among the other 16mm color films which the Ruffners have made is "Catalina Holiday." This picture has received much favorable comment, but has not been entered in amateur competitions because it is longer than most contest rules allow.

Filming Fiesta

Sponsored by the Northern California Council of Amateur Movie Clubs, a "Filming For Fun Fiesta," will be held at the Fairmont Hotel, San Francisco, Saturday and Sunday, October 22 and 23, 1955.

Open to the public as well as to all amateur movie makers, the program includes talks and discussions on such topics as film processing, sound on tape, animation, door script shooting and film editing.

A banquet will be held Saturday evening at which time there will be a screening of National prize-winning films.

to put *mood* on film...

Clark Gable and Jane Russell in "The Tall Men," 20th Century Fox CinemaScope production, filmed with B&L 40mm Baltar CinemaScope Lenses—combined cine anamorphic lens, single focusing adjustment

BALTAR

It's the skill of the master cinematographer that makes filmed sequences tingle with life. And it's experience, too—he insists on the world's finest lenses to give him *exactly* the effects he wants.

ORDER from your professional camera manufacturer, or **WRITE** to Bausch & Lomb Optical Co., 30045 Martin St., Rochester 2, N. Y.

Academy Honorary Award for optical service to the industry

BAUSCH & LOMB

SINCE B&L 1853

A.M.P.A.S.

For *balanced* color...use byron color-correct* prints



Byron color-correct* prints give you color that is never too light — never too dark — color that is always right! Such perfection is a regular service at Byron — backed by efficient personnel, precision equipment, operating in a plant designed for peak performance. Byron quality, *Byron service costs no more,* and is available in 8 hours if necessary. Write, wire, or call today for an early start on your job!

. . . and for *balanced* service byron offers you these 16mm production facilities:

script	*recording*
art	*location photography*
titling	*music library*
animation	*sound stage*
editing	*complete black and white laboratory facilities*
sound effects	*precision magnetic striping*

byron *Studios and Laboratory*

1226 Wisconsin Avenue, N.W., Washington 7, D.C. *DUpont 7-1800*

**Reg. U. S. Patent Office*

SEND FOR YOUR COMPLIMENTARY COPY OF THE 3 ILLUSTRATED BULLETINS ON "PRE-PRINT PREPARATION" AS DEVELOPED AND RECOMMENDED BY THE ASSOCIATION OF CINEMA LABORATORIES